


Adrian Koenig Survey

Part of the SW 1/4 of Section 31,
Town-5-South, Range-6-East,
Duchouquet Township, Auglaize County, Ohio



VICINITY MAP - SECTION 31

tract 1 2.008 acres

0.290 acres in the W 1/2 of the SW 1/4
1.718 acres in the E 1/2 of the SW 1/4
(0.111 acres right-of-way)

Official Record Volume 505
Pages 780 & 782

SW Corner of the
East one-half of
the SW 1/4 of
Section 31

DUCHOUQUET TOWNSHIP
PUSHETA TOWNSHIP

tract 2 2.015 acres

(0.187 acres right-of-way)

road right-of-way line

326.17' N89°41'58"W CANNING FACTORY ROAD (50' R/W) 261.05' N89°41'58"W

tract 3 2.003 acres


(0.150 acres right-of-way)


Joyce Knueve
& Angeline Green
OR Volume 438,
Page 1462 & 1497

NW 1/4, Section 6
Pusheta Township

This plat of survey is an accurate representation of a
field survey, conducted under my direct supervision
on the date shown hereon.


JAMES M. KENT, PS 6792





GRAPHIC SCALE
(IN FEET)
1 inch = 50 ft

kent surveying, inc.
acad - koenig, adrian
drawing #4302
September 29, 2004
revised October 8, 2004

Legend


- Monument Box (found)
- 5/8" re-rod w/cap (set)
- mag-nail (found)
- cotton gin spindle (set)
- 5/8" re-rod w/cap (found)



Denotes approximate location
of inundation created by a
100 YR flood. FIRM Map
Number 39011C0105 C;
Effective Date: Sept. 6, 1989

Basis of bearings is per Auglaize County
GPS of the south line of the SW quarter as
S 89°41'58"E

Adrian Koenig Survey
Tract 1



scale:

SURVEYOR'S DESCRIPTION

Being a part of the southwest quarter of Section 31, Town-5-South, Range-6-East, Duchouquet Township, Auglaize County, Ohio as evidenced by Official Record Volume 438, Page 1462 and 1497, and Official Record Volume 505, Page 780 and 782, and more particularly described as follows:

Commencing for reference at a monument box (found) at the northeast corner of the northwest quarter of Section 6 (Pusheta Township) and the legal centerline of Canning Factory Road; thence, N 89 degrees 41' 58" W along the south line of the southwest quarter of Section 31 and the legal centerline of Canning Factory Road, for a distance of 1127.59 feet to a cotton gin spindle (set), said spindle being the **POINT OF BEGINNING** for the tract herein described;

thence, continuing N 89 degrees 41' 58" W along the aforesaid south line and legal centerline, (passing through a mag-nail found at the southwest corner of the east one-half of the southwest quarter of Section 31 at a distance of 167.65 feet) for a total distance of 192.65 feet to a mag nail (found);


thence, N 00 degrees 29' 49" E (passing through a 5/8" re-rod w/cap found on the north right-of-way line of Canning Factory Road at a distance of 25.00 feet and passing through a 5/8" re-rod w/cap found at a distance of 438.90 feet) for a total distance of 507.33 feet to the centerline of Pusheta Creek;


thence, with the centerline of said Pusheta Creek for the following courses:
S 77 degrees 33' 20" E for a distance of 25.55 feet to the intersection of the centerline of said creek with the west line of the east one-half of the southwest quarter of Section 31;

S 57 degrees 06' 40" E for a distance of 173.41 feet to a point;

S 45 degrees 36' 28" E for a distance of 27.40 feet to a point;

thence, S 00 degrees 17' 30" W and leaving said Pusheta Creek (passing through a 5/8" re-rod w/cap set for reference at a distance of 72.78 feet and a 5/8" re-rod w/cap set on the north right-of-way line of Cemetery Road at a distance of 364.43 feet) for a total distance of 389.43 feet to the **POINT OF BEGINNING**, containing therein **2.008 acres**, of which 0.290 acres in the west one-half of the southwest quarter and 1.718 acres is in the east one-half of the southwest quarter, and 0.111 acres is road right-of-way. Basis of bearings is per Auglaize County GPS depicting the south line of the southwest quarter as S 89 degrees 41' 58" E. Subject to all easements and right-of-way of record. Prepared by James M. Kent, PS 6792 OH with reference hereby made to a plat of survey; Kent Surveying, Inc. drawing #4302 dated September 29, 2004.


James M. Kent, PS 6792




CLIENT	ADRIAN KOENIG	DATE	10-8-04
COUNTY	AUGLAIZE	TOWNSHIP	DUCHOUQUET
SECTION	31	T-5-S; R-6-E	DRAWN BY <u>JMK</u>
SHEET	1	OF 3	DWG. # <u>4302</u>

kent surveying, inc.
P.O. Box 96 - 1750 Bellefontaine Street
Wapakoneta, OH 45895
419-738-5677 fax 419-738-7894

Doc - 31-29A

Adrian Koenig Survey
Tract 2



scale:

SURVEYOR'S DESCRIPTION

Being a part of the southwest quarter of Section 31, Town-5-South, Range-6-East, Duchouquet Township, Auglaize County, Ohio as evidenced by Official Record Volume 438, Page 1462 and 1497 and more particularly described as follows;

Commencing for reference at a monument box (found) at the northeast corner of the northwest quarter of Section 6 (Pusheta Township) and the legal centerline of Canning Factory Road; thence, N 89 degrees 41' 58" W along the south line of the southwest quarter of Section 31 and the legal centerline of Canning Factory Road, for a distance of 801.42 feet to a cotton gin spindle (set), said spindle being the **POINT OF BEGINNING** for the tract herein described;


thence, continuing N 89 degrees 41' 58" W along the aforesaid south line and legal centerline, for a total distance of 326.17 feet to a cotton gin spindle (set);


thence, N 00 degrees 17' 30" E (passing through a 5/8" re-rod w/cap set on the north right-of-way line of Canning Factory Road at a distance of 25.00 feet and passing through a 5/8" re-rod w/cap set at a distance of 317.51 feet) for a total distance of 389.43 feet to the centerline of Pusheta Creek;

thence, with the centerline of said Pusheta Creek for the following courses:

S 43 degrees 36' 28" E for a distance of 179.06 feet to a point;
S 67 degrees 31' 14" E for a distance of 150.31 feet to a point;
N 69 degrees 27' 10" E for a distance of 62.47 feet to a point;

thence, S 00 degrees 17' 17" W and leaving said Pusheta Creek (passing through a 5/8" re-rod w/cap set for reference at a distance of 19.94 feet and a 5/8" re-rod w/cap set on the north right-of-way line of Cemetery Road at a distance of 205.33 feet) for a total distance of 230.33 feet to the **POINT OF BEGINNING**, containing therein **2.015 acres**, of which 0.187 acres is road right-of-way. Basis of bearings is per Auglaize County GPS depicting the south line of the southwest quarter as S 89 degrees 41' 58" E. Subject to all easements and right-of-way of record. Prepared by James M. Kent, PS 6792 OH with reference hereby made to a plat of survey; Kent Surveying, Inc. drawing #4302 dated September 29, 2004.


James M. Kent, PS 6792




CLIENT	ADRIAN KOENIG	DATE	10-8-04
COUNTY	AUGLAIZE	TOWNSHIP	DUCHOUQUET
SECTION	31	T-5-S; R-6-E	DRAWN BY JMK
SHEET	2	OF	3

kent surveying, inc.
P.O. Box 96 - 1750 Bellefontaine Street
Wapakoneta, OH 45895
419-738-5677 fax 419-738-7894

DUC-31-29B

Adrian Koenig Survey
Tract 3



scale:

SURVEYOR'S DESCRIPTION

Being a part of the southwest quarter of Section 31, Town-5-South, Range-6-East, Duchouquet Township, Auglaize County, Ohio as evidenced by Official Record Volume 438, Page 1462 and 1497 and more particularly described as follows:

Commencing for reference at a monument box (found) at the northeast corner of the northwest quarter of Section 6 (Pusheta Township) and the legal centerline of Canning Factory Road; thence, N 89 degrees 41' 58" W along the south line of the southwest quarter of Section 31 and the legal centerline of Canning Factory Road, for a distance of 540.37 feet to a cotton gin spindle (set), said spindle being the **POINT OF BEGINNING** for the tract herein described;

thence, continuing N 89 degrees 41' 58" W along the aforesaid south line and legal centerline, for a total distance of 261.05 feet to a cotton gin spindle (set);

thence, N 00 degrees 17' 17" E (passing through a 5/8" re-rod w/cap set on the north right-of-way line of Canning Factory Road at a distance of 25.00 feet and passing through a 5/8" re-rod w/cap set at a distance of 210.39 feet) for a total distance of 230.33 feet to the centerline of Pusheta Creek;


thence, with the centerline of said Pusheta Creek for the following courses:

N 69 degrees 27' 10" E for a distance of 56.89 feet to a point;


N 49 degrees 40' 49" E for a distance of 149.85 feet to a point;

N 67 degrees 24' 41" E for a distance of 134.54 feet to a point;

thence, S 04 degrees 32' 55" W (passing through a 5/8" re-rod w/cap set for reference at a distance of 20.34 feet, and passing through a 5/8" re-rod w/cap set on the north right-of-way line of Cemetery Road at a distance of 376.50 feet) for a total distance of 401.57 feet to the **POINT OF BEGINNING**, containing therein **2.003 acres**, of which 0.150 acres is road right-of-way. Basis of bearings is per Auglaize County GPS depicting the south line of the southwest quarter as S 89 degrees 41' 58" E. Subject to all easements and right-of-way of record. Prepared by James M. Kent, PS 6792 OH with reference hereby made to a plat of survey; Kent Surveying, Inc. drawing #4302 dated September 29, 2004.



James M. Kent, PS 6792



CLIENT	ADRIAN KOENIG	DATE	10-8-04
COUNTY	AUGLAIZE	TOWNSHIP	DUCHOUQUET
SECTION	31	T-5-S; R-6-E	DRAWN BY
SHEET	3 OF 3	DWG. #	
		4302	

kent surveying, inc.
P.O. Box 96 - 1750 Bellefontaine Street
Wapakoneta, OH 45895
419-738-5677 fax 419-738-7894

DOC - 31-29C