

(Set) Ch: NO5. 44'50" W, 199.11' CENTERLINE CURVE DATA P.I. Sta. 287+22.12 △· /° 58′30″ T. 148.07 R.8594.37 L= 296.11'

5/8 Rebar (found)

PK nail

(found)

S87°47'50"W.

40.11

PK nail

(found)

REFERENCE State R/W Drawing USR 25 Sheet 12 Sta 273+00 to Sta 289+00

## DESCRIPTION

-RR Spike (found)

-PLACE OF

BEGINNING

Being a part of Sidney Pike and also a part of Lots 1, 2, 3 and 4 in John C. Bothe's Subdivision of Lots 9 \$ 10 Wilds Sub W/2,3E/4 Section 32, T-5-S, R-6-E, City of Wapakoneta, Auglaize County, Ohio and more particularly described as follows:

N 05°05'00"W, 439.20

BEGINNING at a railroad spike found at intersection of the centerlines of Willipie St. (formerly Sidney Pike) and Krein Avenue in said City of Wapakoneta; thence 'N 88° 13'25" E with the centerline of Krein Avenue, 30.05 feet to a point; thence \$ 05°05'00" E, 33.05 feet to a dainch rebar set at the intersection of the south right of way line of said Krein Avenue with the proposed east right of way line of Willipie Street; thence southeasterly the following three courses that define the proposed east right of way line of said Willipie Street: 3 05°05'00" E, 225.10 feet to a chiseled "x" in a concrete drive approach; S 08° 16' 35" E, 179.59 feet to a % inch rebar set 40.00 feef east of the P.T. of a centerline curve for said Willipie Street; thence southeasterly on a non-tangent curve to the left having a radius of 8554.37 feet (passing through a 48 inch rebar found on the arc at 66.13 feet) an arc length of 20113 feet to a 5/8 inch found (chord for said curve being S 08°45'26" E, 201.13 feet); thence S 87°47'49" W on a non-radial line, 40.11 feet to a PK nail found on the centerline of Willipie Street; thence northwesterly on a non-tangent curve to the right having a radius of 8594.37 feet (passing through a PK found on the arc at 135.00 feet) an arc length of 199.11 feet to a PK nail set at the PT of said curve (chord for said curve being N 05°44'50" W, 199.11 feet); thence N 05°05'00" W continuing with said centerline of Willipie Street, 439.20 feet to the PLACE OF BEGINNING containing 0.506 acre.

I hereby certify that this plat is based on a true and accurate survey made by me in January 1990 and that all markers are in place.



Richard D. Moine Registered Surveyor L.S. 6440 KÜCK and MORRISEY, Inc. Consulting Engineers & Surveyors

## DEDICATION

Smithey - McCormick an Ohio General Partnership

554.37', Arc 201.13

R: 8594.37', Arc: 199.11

OR Vol. 43 Pg. 221

Pg. 795

5/8" Rebar

Vol. 265 6

& Willipia St.

The undersigned OWNERS of the land contained in the hereon plat, hereby adopts said plat and dedicates the land contained within the strip described to the use and benefit of the public forever.

Smithey - McCormick J-B Tool & Machine, Inc.

## ACKNOWLEDGEMENT

STATE OF OHIO AUGLAIZE COUNTY Before me, a Notary Public in and for said State and County, did personally appear the above signed OWNERS, who acknowledged that they did sign the hereon plat and the same is their free act and deed. In testimony whereof, I have hereunto set my hand and official seal this 8th day of March 1990.

Susan a. Morrisey My commission expires December 28, 1993

APPROVAL, CITY OF WAPAKONETA Approved and accepted this \_\_\_\_\_day of \_\_\_\_\_\_,1990

SAFETY - SERVICE DIRECTOR

COUNTY	PECOPI	DERIS	CERTIF	FICATION

iled fo	or	Record	this	day	of			1990	), at	o'clock_	^1.
		this		of		,1990	in	Plat	Cabinet_	Slide_	