The undersigned, being all of the owners of the real estate of the following described territory situated in the County of Auglaize, and adjacent LEO & LUELLA TOPP to the Village of New Bremen, Ohio, to-wit: D. B. 229, PG. 427 TRACT I Situated in the Southwest Quarter of Section 10, Township 7 South, Range 4 East, German Township, Auglaize County, Ohio and part of an 8.953 acre tract as described in Auglaize County Deed Records Volume 218, page 863, and being more particularly described as follows: Commencing at a cast iron monument at the Southeast corner of the Southwest Quarter of said Section 10; thence N. 89°-43-00 W. South 89°-57'-30" West 921.75 feet along the South line of said section, said line also being the centerline of 2.0' S. OF MON. State Route 274, to a P.K. nail, said nail being the TRUE POINT OF BEGINNING for the traot described herein; thence CORNER 2.0'S, OF continuing South 89°-57'-30" West 400.56 feet to a P.K. nail; thence North 00°-01'-30" East 30.00 feet to a concret CORNER monument; thence North 89°-57'-30" East 400.56 feet along the North right-of-way of said S.R. 274 to a concrete monument; thence South 00°-01'-30" West 30.00 feet to the point of beginning, containing 0.276 acres, more or less, and being subject to all legal highway and easements of record. TRACT II Situated in the Southwest Quarter of Section 10, Township 7 South, Range 4 East, German Township, Auglaize County, Ohio and part of a 9.27 acre tract as described in Auglaize County Deed Records Volume 199, page 825, and being more particularly described as follows: Commencing at a cast iron monument at the Southeast corner of the Southwest Quarter of said Section 10; MADELLA TOMHAFE thence South 89°-57'-30" West 1322.31 feet along the South line of said section, said line also being the centerlin CROWN CONTROLS of State Route 274 to a P.K. nail, said nail being the TRUE POINT OF BEGINNING for the tract described herein; D.B. 136, PG. 439 thence continuing South 89°-57'-30" West 324.85 feet to a point; thence North 00°-01'-30" East 538.81 feet to a CORPORATION point; thence North 89°-50'-30" East 324.85 feet along the North line of said 9.27 acre tract to a concrete D.B. 229, PG. 255 monument; thence South 00°-01'-30" West 539.47 feet along the East line of said 9.27 acre tract to the point of beginning, containing 4.021 acres, more or less, and being subject to all legal highway and easements of record. - 565.56 -S. 89°-57-30° W. TRACT III Situated in the Southwest Quarter of Section 10, Township 7 South, Range 4 NORTH CORPORATION LINE-East, German Township, Auglaize County, Ohio, and part of a 7.748 acre tract as described in Auglaize County Deed Records Volume 229, page 255, and also a part of a tract as described in Volume 248, page 57, and being more particularly described as follows: Commencing at a cast iron monument at the Southeast corner of the Southwest Quarter of said Section 10; thence South 89°-57'-30" West 1322.31 feet along the South line of said section, said line also being the centerline of State Route 274, to a P.K. nail; thence North 00°-01'-30" East 539.47 feet along the East line of a 9.27 acre tract as described in Auglaiz County Deed Records Volume 199 page 825 to a concrete monument, said monument being the TRUE POINT OF BEGINNING for the tract described herein; thence continuing North 00°-01'-30" East 489.58 feet to a point; thence N.89°50'-30'E. -/32.4.85°-North 89°-43'-00" West 324.85 feet along the North line of said 7.748 acre tract to a point; thence South 00°-01'-30" West 492.08 feet to a point; thence North 89°-50'-30" East 324.85 feet along the South line of said 7.748 acre tract to the point of beginning containing 3.660 acres, more or CROWN CONTROLS less, and being subject to all legal highways and easements of record. CORPORATION D. B. 218, PG. 863 Situated in the Southwest Quarter of Section 10, Township 7 South, range 4 East, German Township, Auglaize County, Ohio and part of an 8.953 acre tract as described in Auglaize County Deed Records Volume 218, page 863, and being more particularly described as follows: Commenceing at a cast iron monument at the Southeast corner of the CROWN CONTROLS Southwest Quarter of said Section 10; thence South 89°-57'-30" West 756.75 CORPORATION feet along the South line of said section, said line also being the centerline of State Route 274, to a P.K. nail, said nail being the TRUE POINT OF D.B.199, P.G. 825 ACRES BEGINNING for the tract described herein; thence continuing South 89°-57'-30" West 55.00 feet to a P.K. nail; thence North 00°-01'-30" East 30.00 feet 110.00 along the East line of a tract as described in Volume 221, Page 859, to a N.89°-57'- 30'E. concrete monument; thence North 89-57'-30" East 55.00 feet along the North right-of-way line of said State Route 274 to a point; thence South 00°-01'-D.B. 221 30" West 30.00 feet to the point of beginning, containing 0.038 acres, more PG.859 or less, and being subject to all legal highways and easements of record. The above four (4) descriptions were based on existing deed and survey information. No field work was performed and no monuments were set at this __ 90.00′_ VILLAGE OF NEW BREMEN Prepared by: Richard T.Mote, Registered Surveyor #5552, November, 1979 D.B.227 MOTE-GARRISON & ASSOCIATES INC., 306 Sycamore Street, Greenville, Ohio, 45331 PG. 585 TRACT IV 0.038 Respectfully petitions for the annexation of the above described 794.36 ACRES territory to the Village of New Bremen, Ohio. E ST. RT. 274 S. 89-57-30 W. 400.56 CAST IRON MONUMENT AT S.E. CORNER OF S.W. S.89-57-30 W. 1/4 OF SECTION 10. -756.75[']-VILLAGE OF NEW BREMEN LEGEND: X P.K. NAIL e IRON PIN A CONC. MONUMENT CAST IRON Ø R.R. SPIKE

1		REVISIONS					·
	TOLERANCES						
L		NO.	DATE	BY	ANNEXATION TO VILLAGE OF NEW BREMEN CROWN CONTROLS CORPORATION		
	DECIMAL	1					
1	± .						
I	FRACTIONAL	2					
	±	. 3			DRAWN BY	I"=100'	MATERIAL
	ANGULAR	4			СНК.	8-13-80	DRAWING NO.
	±	5			TRACED	APP'D	80-100