





# Morris Farm Survey

Situated in the Northeast Quarter  
of Section 9, Goshen Township,  
Town-6-South, Range-7-East,  
Auglaize County, Ohio



- Legend**
- Iron pin (set)
  - Iron pin (found)
  - ▲ P.K. Nail (set)
  - △ P.K. Nail (found)
  - 6" Concrete End Post
  - × Point in Centerline of Ditch
  - Monument Box
  - ODOT Concrete Monument



## Deed References

- Deed Volume 29, Page 257  
Auglaize County Recorder's Office
- Deed Volume 50, Page 477  
Auglaize County Recorder's Office
- Deed Volume 61, Page 557  
Auglaize County Recorder's Office
- Deed Volume 136, Page 379  
Auglaize County Recorder's Office
- Deed Volume 259, Page 447  
Auglaize County Recorder's Office
- Deed Volume OR219, Page 32  
Auglaize County Recorder's Office

## Survey References

- Survey Book 1, Page 204  
Auglaize County Engineer's Tax Map Office
- Survey Book K, Page 125  
Auglaize County Engineer's Tax Map Office
- Survey By Kuck & Morrissey (5/5/89)  
3.716 Acres for Donald Barnes
- Survey By Lee Surveying & Mapping Co. (3/26/85)  
2.352 Acres for Linda Barnes

## Ditch Traverse Table

①	S. 36°-24'-43" E.	99.81'
②	S. 39°-08'-05" E.	99.93'
③	S. 47°-44'-56" E.	145.77'
④	S. 48°-39'-30" E.	145.55'
⑤	S. 76°-40'-39" E.	93.89'
⑥	S. 82°-06'-43" E.	104.09'
⑦	S. 84°-50'-44" E.	156.87'
⑧	S. 83°-37'-58" E.	155.13'
⑨	N. 81°-31'-37" E.	149.80'
⑩	N. 75°-06'-19" E.	87.95'



Southeast Corner of the  
Northeast Quarter of  
Section 9, Goshen Twp.

Attest:

*Ted K. Schnell*

Ted K. Schnell  
Professional Engineer  
Professional Surveyor

1/30/95  
date



30 foot right-of-way as described  
in Miscellaneous Volume 1, Page 240


Ted K. Schnell Professional Engineer Professional Surveyor		
REVISIONS		
NO.	DATE	BY
1		
2		
3		
4		
5		
Morris Farm Suvey		
Section 9, Goshen Twp.		
DRAWN BY	SCALE	DRAWING NO.
Kevin	Shown	
CHK'D	DATE	
Greg	July 29, 1995	
TRACED	APP'D	
1 OF 1		

GOS-9-1

Civil Engineering  
Land Surveying

R.R. No. 3  
11873 Glynn Road  
Wapakoneta, Ohio 45895  
phone - (419) 736-4750

Ted Kevin Schnell  
Registered Professional Engineer  
Registered Professional Surveyor



client MORRIS ESTATE  
county AUGLAIZE township GOSHEN  
section 9 T- 6 - S, R- 7 - E  
drawn by Kevin date 7/30/95  
checked by \_\_\_\_\_ sheet 1 of 2

SURVEYOR'S DESCRIPTION FOR PARCEL "A"  
46.722 ACRE PARCEL

THE FOLLOWING DESCRIBED PARCEL OF LAND IS SITUATED IN THE NORTHEAST QUARTER OF SECTION 9, GOSHEN TOWNSHIP, TOWN-6-SOUTH, RANGE-7-EAST, AUGLAIZE COUNTY, OHIO, AND IS MORE PARTICULARLY DESCRIBED AS FOLLOWS:

COMMENCING AT AN AUGLAIZE COUNTY MONUMENT BOX LOCATED AT THE NORTHWEST CORNER OF THE NORTHEAST QUARTER OF SECTION 9, GOSHEN TOWNSHIP, TOWN-6-SOUTH, RANGE-7-EAST, AUGLAIZE COUNTY, OHIO;

THENCE WITH A BEARING OF N. 89°-42'-23" E. ALONG THE NORTH LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9 FOR A DISTANCE OF 272.58 FEET TO A P.K. NAIL/SHINER ON THE CENTERLINE OF STATE ROUTE 33 AND THE PLACE OF BEGINNING;

THENCE CONTINUING WITH A BEARING OF N. 89°-42'-23" E. ALONG THE NORTH LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9 FOR A DISTANCE OF 1,299.09 FEET TO AN IRON PIN;

THENCE WITH A BEARING OF S. 36°-24'-43" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 99.81 FEET TO A POINT;

THENCE WITH A BEARING OF S. 39°-08'-05" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 99.93 FEET TO A POINT;

THENCE WITH A BEARING OF S. 47°-44'-56" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 145.77 FEET TO A POINT;

THENCE WITH A BEARING OF S. 48°-39'-30" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 145.55 FEET TO A POINT;

THENCE WITH A BEARING OF S. 76°-40'-39" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 93.89 FEET TO A POINT;

THENCE WITH A BEARING OF S. 82°-06'-43" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 104.09 FEET TO A POINT;

THENCE WITH A BEARING OF S. 84°-50'-44" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 156.87 FEET TO A POINT;

THENCE WITH A BEARING OF S. 83°-37'-58" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 155.13 FEET TO A POINT;

THENCE WITH A BEARING OF N. 81°-31'-37" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 149.80 FEET TO A POINT;

THENCE WITH A BEARING OF N. 75°-06'-19" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 87.95 FEET TO A POINT ON THE EAST LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9;

SURVEYOR'S DESCRIPTION FOR PARCEL "A"  
46.722 ACRE PARCEL

(CONTINUED)

THENCE WITH A BEARING OF S. 00°-31'-56" W. ALONG THE EAST LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9 FOR A DISTANCE OF 775.75 FEET TO A POINT, SAID POINT BEING REFERENCED BY A CONCRETE END POST FOUND AT S. 89°-42'-23" W. AT A DISTANCE OF 0.52 FEET;

THENCE WITH A BEARING OF S. 89°-42'-23" W. FOR A DISTANCE OF 1,953.54 FEET TO A P.K. NAIL/SHINER ON THE CENTERLINE OF STATE ROUTE 33, AND PASSING THRU AN IRON PIN ON THE EASTERLY RIGHT-OF-WAY LINE OF STATE ROUTE 33 AT 1,921.71 FEET;

THENCE WITH A BEARING OF N. 19°-49'-27" W. ALONG THE CENTERLINE OF STATE ROUTE 33 FOR A DISTANCE OF 507.76 FEET TO A P.K. NAIL/SHINER;

THENCE WITH A BEARING OF N. 89°-42'-44" E. FOR A DISTANCE OF 455.49 FEET TO AN IRON PIN, AND PASSING THRU AN IRON PIN FOR REFERENCE ONLY AT 31.43 FEET;

THENCE WITH A BEARING OF N. 00°-28'-04" W. FOR A DISTANCE OF 221.15 FEET TO AN IRON PIN;

THENCE WITH A BEARING OF S. 89°-42'-27" W. FOR A DISTANCE OF 533.25 FEET TO A P.K. NAIL/SHINER ON THE CENTERLINE OF STATE ROUTE 33, AND PASSING THRU AN IRON PIN FOR REFERENCE ONLY AT 503.10 FEET;


THENCE WITH A BEARING OF N. 19°-49'-27" W. ALONG THE CENTERLINE OF STATE ROUTE 33 FOR A DISTANCE OF 483.90 FEET TO A P.K. NAIL/SHINER AND THE PLACE OF BEGINNING;

CONTAINING IN ALL 46.722 ACRES OF LAND, OF WHICH, 0.683 ACRE BEING PREVIOUSLY DEDICATED FOR HIGHWAY PURPOSES AS PER MISCELLANEOUS VOLUME 1, PAGE 240, AUGLAIZE COUNTY RECORDER'S OFFICE.

PREPARED BY:

*Ted K. Schnell*


TED K. SCHNELL  
PROFESSIONAL ENGINEER  
PROFESSIONAL SURVEYOR



Civil Engineering  
Land Surveying

R.R. No. 3  
11873 Glynnwood Road  
Wapakoneta, Ohio 45395  
phone - (419) 738-4758

Ted Kevin Schnell  
Registered Professional Engineer  
Registered Professional Surveyor



client MORRIS ESTATE  
county AUGLAIZE township GOSHEN  
section 9 T- 6 -S, R- 7 -E  
drawn by KEVIN date 7/30/95  
checked by \_\_\_\_\_ sheet 1 of 1

SURVEYOR'S DESCRIPTION FOR PARCEL "B"  
8.259 ACRE PARCEL

THE FOLLOWING DESCRIBED PARCEL OF LAND IS SITUATED IN THE NORTHEAST QUARTER OF SECTION 9, GOSHEN TOWNSHIP, TOWN-6-SOUTH, RANGE-7-EAST, AUGLAIZE COUNTY, OHIO, AND IS MORE PARTICULARLY DESCRIBED AS FOLLOWS:

COMMENCING AT AN AUGLAIZE COUNTY MONUMENT BOX LOCATED AT THE NORTHEAST CORNER OF THE NORTHEAST QUARTER OF SECTION 9, GOSHEN TOWNSHIP, TOWN-6-SOUTH, RANGE-7-EAST, AUGLAIZE COUNTY, OHIO AND THE PLACE OF BEGINNING;

THENCE WITH A BEARING OF S. 00°-31'-56" W. ALONG THE EAST LINE OF SAID NORTHEAST QUARTER OF SECTION 9, GOSHEN TOWNSHIP, FOR A DISTANCE OF 380.09 FEET TO A POINT IN THE CENTERLINE OF AN OPEN DITCH, AND PASSING THRU AN IRON PIN FOR REFERENCE AT 20.00 FEET AND AT 370.09 FEET;

THENCE WITH A BEARING OF S. 75°-06'-19" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 87.95 FEET TO A POINT;

THENCE WITH A BEARING OF S. 81°-31'-37" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 149.80 FEET TO A POINT;

THENCE WITH A BEARING OF N. 83°-37'-58" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 155.13 FEET TO A POINT;

THENCE WITH A BEARING OF N. 84°-50'-44" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 156.87 FEET TO A POINT;

THENCE WITH A BEARING OF N. 82°-06'-43" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 104.09 FEET TO A POINT;

THENCE WITH A BEARING OF N. 76°-40'-39" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 93.89 FEET TO A POINT;

THENCE WITH A BEARING OF N. 48°-39'-30" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 145.55 FEET TO A POINT;

THENCE WITH A BEARING OF N. 47°-44'-56" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 145.77 FEET TO A POINT;

THENCE WITH A BEARING OF N. 39°-08'-05" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 99.93 FEET TO A POINT;


THENCE WITH A BEARING OF N. 36°-24'-43" W. FOR A DISTANCE OF 99.81 FEET TO AN IRON PIN ON THE NORTH LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9, GOSHEN TOWNSHIP;

THENCE WITH A BEARING OF N. 89°-42'-23" E. ALONG THE NORTH LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9, GOSHEN TOWNSHIP, FOR A DISTANCE OF 1,081.07 FEET TO AN AUGLAIZE COUNTY MONUMENT BOX AND THE PLACE OF BEGINNING.

CONTAINING IN ALL 8.259 ACRES OF LAND SUBJECT TO ALL LEGAL EASEMENTS, RESERVATIONS, OR RESTRICTIONS, IF ANY, UPON SAID PREMISES.

PREPARED BY:


Ted K. Schnell  
TED K. SCHNELL  
PROFESSIONAL ENGINEER



Civil Engineering  
Land Surveying

R.R. No. 3  
11873 Glynnwood Road  
Wapakoneta, Ohio 45395  
phone - (419) 738-4758

Ted Kevin Schnell  
Registered Professional Engineer  
Registered Professional Surveyor



client MORRIS ESTATE  
county AUGLAIZE township GOSHEN  
section 9 T- 6 -S, R- 7 -E  
drawn by KEVIN date 7/30/95  
checked by \_\_\_\_\_ sheet 1 of 2

SURVEYOR'S DESCRIPTION FOR PARCEL "A"  
46.722 ACRE PARCEL

THE FOLLOWING DESCRIBED PARCEL OF LAND IS SITUATED IN THE NORTHEAST QUARTER OF SECTION 9, GOSHEN TOWNSHIP, TOWN-6-SOUTH, RANGE-7-EAST, AUGLAIZE COUNTY, OHIO, AND IS MORE PARTICULARLY DESCRIBED AS FOLLOWS:

COMMENCING AT AN AUGLAIZE COUNTY MONUMENT BOX LOCATED AT THE NORTHWEST CORNER OF THE NORTHEAST QUARTER OF SECTION 9, GOSHEN TOWNSHIP, TOWN-6-SOUTH, RANGE-7-EAST, AUGLAIZE COUNTY, OHIO;

THENCE WITH A BEARING OF N. 89°-42'-23" E. ALONG THE NORTH LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9 FOR A DISTANCE OF 272.58 FEET TO A P.K. NAIL/SHINER ON THE CENTERLINE OF STATE ROUTE 33 AND THE PLACE OF BEGINNING;

THENCE CONTINUING WITH A BEARING OF N. 89°-42'-23" E. ALONG THE NORTH LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9 FOR A DISTANCE OF 1,299.09 FEET TO AN IRON PIN;

THENCE WITH A BEARING OF S. 36°-24'-43" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 99.81 FEET TO A POINT;

THENCE WITH A BEARING OF S. 39°-08'-05" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 99.93 FEET TO A POINT;

THENCE WITH A BEARING OF S. 47°-44'-56" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 145.77 FEET TO A POINT;

THENCE WITH A BEARING OF S. 48°-39'-30" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 145.55 FEET TO A POINT;

THENCE WITH A BEARING OF S. 76°-40'-39" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 93.89 FEET TO A POINT;

THENCE WITH A BEARING OF S. 82°-06'-43" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 104.09 FEET TO A POINT;

THENCE WITH A BEARING OF S. 84°-50'-44" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 156.87 FEET TO A POINT;

THENCE WITH A BEARING OF S. 83°-37'-58" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 155.13 FEET TO A POINT;

THENCE WITH A BEARING OF N. 81°-31'-37" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 149.80 FEET TO A POINT;

THENCE WITH A BEARING OF N. 75°-06'-19" E. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 87.95 FEET TO A POINT ON THE EAST LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9;



2/2

SURVEYOR'S DESCRIPTION FOR PARCEL "A"  
46.722 ACRE PARCEL

(CONTINUED)

THENCE WITH A BEARING OF S. 00°-31'-56" W. ALONG THE EAST LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9 FOR A DISTANCE OF 775.75 FEET TO A POINT, SAID POINT BEING REFERENCED BY A CONCRETE END POST FOUND AT S. 89°-42'-23" W. AT A DISTANCE OF 0.52 FEET;

THENCE WITH A BEARING OF S. 89°-42'-23" W. FOR A DISTANCE OF 1,953.54 FEET TO A P.K. NAIL/SHINER ON THE CENTERLINE OF STATE ROUTE 33, AND PASSING THRU AN IRON PIN ON THE EASTERLY RIGHT-OF-WAY LINE OF STATE ROUTE 33 AT 1,921.71 FEET;

THENCE WITH A BEARING OF N. 19°-49'-27" W. ALONG THE CENTERLINE OF STATE ROUTE 33 FOR A DISTANCE OF 507.76 FEET TO A P.K. NAIL/SHINER;

THENCE WITH A BEARING OF N. 89°-42'-44" E. FOR A DISTANCE OF 455.49 FEET TO AN IRON PIN, AND PASSING THRU AN IRON PIN FOR REFERENCE ONLY AT 31.43 FEET;


THENCE WITH A BEARING OF N. 00°-28'-04" W. FOR A DISTANCE OF 221.15 FEET TO AN IRON PIN;

THENCE WITH A BEARING OF S. 89°-42'-27" W. FOR A DISTANCE OF 533.25 FEET TO A P.K. NAIL/SHINER ON THE CENTERLINE OF STATE ROUTE 33, AND PASSING THRU AN IRON PIN FOR REFERENCE ONLY AT 503.10 FEET;

THENCE WITH A BEARING OF N. 19°-49'-27" W. ALONG THE CENTERLINE OF STATE ROUTE 33 FOR A DISTANCE OF 483.90 FEET TO A P.K. NAIL/SHINER AND THE PLACE OF BEGINNING;


CONTAINING IN ALL 46.722 ACRES OF LAND, OF WHICH, 0.683 ACRE BEING PREVIOUSLY DEDICATED FOR HIGHWAY PURPOSES AS PER MISCELLANEOUS VOLUME 1, PAGE 240, AUGLAIZE COUNTY RECORDER'S OFFICE.

PREPARED BY: Ted K. Schnell  
TED K. SCHNELL  
PROFESSIONAL ENGINEER  
PROFESSIONAL SURVEYOR



Civil Engineering  
Land Surveying

R.R. No. 3  
11873 Glynwood Road  
Wapakoneta, Ohio 45495  
phone - (419) 738-4758



Ted Kevin Schnell  
Registered Professional Engineer  
Registered Professional Surveyor

client MORRIS ESTATE  
county AUGLAIZE township GOSHEN  
section 9 T- 6 -S, R- 7 -E  
drawn by Kevin date 7/30/95  
checked by \_\_\_\_\_ sheet 1 of 1

SURVEYOR'S DESCRIPTION FOR PARCEL "B"  
8.259 ACRE PARCEL

THE FOLLOWING DESCRIBED PARCEL OF LAND IS SITUATED IN THE NORTHEAST QUARTER OF SECTION 9, GOSHEN TOWNSHIP, TOWN-6-SOUTH, RANGE-7-EAST, AUGLAIZE COUNTY, OHIO, AND IS MORE PARTICULARLY DESCRIBED AS FOLLOWS:

COMMENCING AT AN AUGLAIZE COUNTY MONUMENT BOX LOCATED AT THE NORTHEAST CORNER OF THE NORTHEAST QUARTER OF SECTION 9, GOSHEN TOWNSHIP, TOWN-6-SOUTH, RANGE-7-EAST, AUGLAIZE COUNTY, OHIO AND THE PLACE OF BEGINNING;

THENCE WITH A BEARING OF S. 00°-31'-56" W. ALONG THE EAST LINE OF SAID NORTHEAST QUARTER OF SECTION 9, GOSHEN TOWNSHIP, FOR A DISTANCE OF 380.09 FEET TO A POINT IN THE CENTERLINE OF AN OPEN DITCH, AND PASSING THRU AN IRON PIN FOR REFERENCE AT 20.00 FEET AND AT 370.09 FEET;

THENCE WITH A BEARING OF S. 75°-06'-19" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 87.95 FEET TO A POINT;

THENCE WITH A BEARING OF S. 81°-31'-37" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 149.80 FEET TO A POINT;

THENCE WITH A BEARING OF N. 83°-37'-58" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 155.13 FEET TO A POINT;

THENCE WITH A BEARING OF N. 84°-50'-44" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 156.87 FEET TO A POINT;

THENCE WITH A BEARING OF N. 82°-06'-43" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 104.09 FEET TO A POINT;

THENCE WITH A BEARING OF N. 76°-40'-39" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 93.89 FEET TO A POINT;

THENCE WITH A BEARING OF N. 48°-39'-30" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 145.55 FEET TO A POINT;

THENCE WITH A BEARING OF N. 47°-44'-56" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 145.77 FEET TO A POINT;

THENCE WITH A BEARING OF N. 39°-08'-05" W. ALONG THE CENTERLINE OF AN OPEN DITCH FOR A DISTANCE OF 99.93 FEET TO A POINT;

THENCE WITH A BEARING OF N. 36°-24'-43" W. FOR A DISTANCE OF 99.81 FEET TO AN IRON PIN ON THE NORTH LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9, GOSHEN TOWNSHIP;

THENCE WITH A BEARING OF N. 89°-42'-23" E. ALONG THE NORTH LINE OF THE NORTHEAST QUARTER OF SAID SECTION 9, GOSHEN TOWNSHIP, FOR A DISTANCE OF 1,081.07 FEET TO AN AUGLAIZE COUNTY MONUMENT BOX AND THE PLACE OF BEGINNING.

CONTAINING IN ALL 8.259 ACRES OF LAND SUBJECT TO ALL LEGAL EASEMENTS, RESERVATIONS, OR RESTRICTIONS, IF ANY, UPON SAID PREMISES.

PREPARED BY: Ted K. Schnell  
TED K. SCHNELL  
PROFESSIONAL ENGINEER

