


Due to the fact that the stones at the center of the section and the East 1/4 point were not found, a survey was done of the entire perimeter of Section 14 with all 1/2 and 1/4 section lines being established according to Ohio Law for reestablishing lost corners. Note that dimensions to existing fence lines are shown at all corners set relative to the established 1/2 and 1/4 section lines. In researching the origin of the existing deed as found in Volume 210, Page 727 of the County Records Office, the first split that occurred in 1855 of the 20+ Acres in the Northeast Quarter is recorded in Volume 13, Page 419 of the Records Office and reads that the width be exactly 20 rods (330.00 feet) and not the W1/2 W1/2 W1/2 of the NE 1/4 as the existing deed reads. I therefore held the 330.00 feet as the full width of the tract in the Northeast Quarter as shown on the survey.



ATTEST: *Doug Reinhart*
Doug Reinhart
Professional Surveyor # 6507

AUGLAIZE COUNTY RECORDERS CERTIFICATE
No. 7498

Filed for record this 8 day of December, 1982,
at 1:20 P.M., and recorded in Auglaize County
Records Office Plat Cabinet A, Page 163, Wapakoneta,
Ohio.

Markus E. Schumann
Auglaize County Recorder

SURVEYORS DESCRIPTIONS

The following described parcels of ground are part of the Northeast and Northwest Quarters of Section 14, Pusheta Township, Township Six (6) South, Range Six (6) East, Auglaize County, Ohio and are more particularly described as follows:

NORTH TRACT 38.76 ACRES

The PLACE OF BEGINNING is a monument box at the Northeast corner of the Northwest quarter of Section 14, Pusheta Township, said box being in the centerline of Township Road # 120 (Pusheta Rd.). Thence N89°-54'-20"W along the north line of Section 14 and the centerline of T.R. # 120 a distance of 1322.52 feet to a spike;
Thence S00°-29'-10"W a distance of 985.00 feet to an iron pin;
Thence S87°-27'-30"E a distance of 528.59 feet to an iron pin;
Thence S82°-02'-20"E a distance of 527.17 feet to an iron pin;
Thence N90°-00"E a distance of 571.24 feet to an iron pin in the West line of a proposed 30.00' access drive;
Thence N00°-30'-15"E along said drive through an iron pin at 1057.94 in the south right-of-way line of T.R. # 120 for a total distance of 1077.94 feet to a spike in the north line of Section 14 and the centerline of T.R. # 120;
Thence N89°-44'-40"W along said section line and centerline a distance of 300.00 feet to a monument box and the PLACE OF BEGINNING.

The above described parcel of ground contains 38.76 Acres of which 0.74 Acres has been previously dedicated for road right-of-ways. The above described parcel is subject to all previous easements of record. Previous deed reference: Volume 210, Page 727, Auglaize County Records Office. Survey Plat recorded in Cabinet A, Page 163, Auglaize County Records Office. 7.43 Acres of the above described tract is located in the Northeast Quarter with the balance being in the NW Quarter.

**SOUTH TRACT 62.00 ACRES
(2.64 ACRES INCLUDED)**


Commencing at a monument box at the Northeast corner of the Northwest Quarter of Section 14, Pusheta Township, said box being in the centerline of Township Road # 120 (Pusheta Road); Thence S89°-44'-40"E along the North line of Section 14 and the centerline of T.R. # 120 a distance of 300.00 feet to a spike and the PLACE OF BEGINNING;
Thence continuing S89°-44'-40"E along said section line and centerline a distance of 30.00 feet to a spike;
Thence S00°-30'-15"W a distance of 2655.33 feet to an iron pin in the East-West half-section line of Section 14;
Thence N89°-56'-40"W along said half-section line passing through the center of Section 14 at 330.00 feet for a total distance of 1651.66 feet to an iron pin;
Thence N00°-29'-10"E a distance of 1672.37 feet to an iron pin;
Thence S87°-27'-30"E a distance of 528.59 feet to an iron pin;
Thence S82°-02'-20"E a distance of 527.17 feet to an iron pin;
Thence N90°-00"E a distance of 571.24 feet to an iron pin in the West side of a 30.00' access drive;
Thence N00°-30'-15"E along the West side of said 30.00' drive through an iron pin in the South right-of-way of T.R. # 120 at 1057.94 feet for a total distance of 1077.94 feet to a spike in the centerline of T.R. # 120 and the PLACE OF BEGINNING.

The above described parcel contains 62.00 Acres of which 0.01 Acres has been previously dedicated for road right-of-way purposes. The above described parcel is subject to all easements of record. 12.69 Acres of the above described parcel is contained in the Northeast Quarter with the balance being in the Northwest Quarter. Previous deed reference: Volume 210, Page 727, Auglaize County Records Office. Survey filed in Cabinet A, Page 163, Auglaize County Records Office.

2.64 ACRE TRACT

Commencing at a monument box at the Northeast corner of the Northwest Quarter of Section 14, Pusheta Township, said box being in the centerline of Township Road # 120 (Pusheta Road); Thence S89°-44'-40"E along the north line of Section 14 and the centerline of T.R. # 120 a distance of 300.00 feet to a spike; Thence S00°-30'-15"W a distance of 1077.94 feet to an iron pin and the PLACE OF BEGINNING;
Thence continuing S00°-30'-15"W a distance of 403.33 feet to a point on the top of an existing open ditch;
Thence N54°-36'-30"W along the top of the bank of an open ditch a distance of 696.37 feet to an iron pin;
Thence N90°-00"E a distance of 571.24 feet to an iron pin and the PLACE OF BEGINNING.

The above described parcel of ground contains 2.64 Acres and is subject to all easements of record. 2.04 Acres of the above described tract being in the Northeast Quarter and 0.6 Acres being in the Northwest Quarter of Section 14. Survey filed in Cabinet A, Page 163, Auglaize County Records Office.



ATTEST: *Doug Reinhart*
Doug Reinhart
Professional Surveyor # 6507
Professional Engineer # 44670

| TOLERANCES (EXCEPT AS NOTED) | REVISIONS | | | DRAWN BY John Jauert | | SCALE 1"=200' | | MATERIAL | |
|---------------------------------|-----------|------|----|-------------------------|--|------------------|--|-----------------------|--|
| | NO. | DATE | BY | | | | | | |
| DECIMAL | 1 | | | CHK'D D. Reinhart | | DATE 12-7-82 | | DRAWING NO. 82-306 | |
| FRACTIONAL | 2 | | | | | | | | |
| ANGULAR | 3 | | | TRACED | | APP'D | | | |
| | 4 | | | | | | | | |
| | 5 | | | | | | | | |