ZWIEBEL ESTATE SURVEY N.E. Corner, N.E. Quarter, -Being the part of the Southwest & Southeast Quarters of Section 14 Section 14, Pusheta Township, Town 6 South, Range 6 East, Auglaize County, Ohio. IP Found 0.33' North of Line North Line of the Southwest Quarter of Section 14 North Line of the Southeast Quarter of Section 14 S.89°53'46"E SURVEYOR'S DESCRIPTION FOR TRACT TWO, 3.802 ACRES P.F. Leibold (Archbishop of Cincinnati) N.E. Corner, Deed Vol. 205. N.W. Corner, S.E. Quarter, S.W. Quarter, Page 828. The following described tract of land is part of the Southeast Quarter of Section 14, Town 6 South, Range 6 East, Pusheta Township, Auglaize County, Ohio and is more particularly described as follows: Section 14 Section 14 Commencing at a Monument Box found at the Southwest corner of the South—east Quarter of Section 14, Pusheta Township and in the centerline of County Road 110 (Fryburg East Road); thence S.89°52'04"E. along the centerline of County Road 110 and the South line of the Southeast Quarter, a distance of 421.33 feet to a Mag Nail found which is the SURVEYOR'S DESCRIPTION FOR TRACT ONE, 259.311 ACRES LOCATION PLAN PLACE OF BEGINNING for the tract of land herein described; thence N.01°06'31"E. a distance of 672.00 feet to an iron pin found, passing thru an iron pin found at 25.00 feet in the North right—of—way line of County Road 110; thence S.89°52'04"E., parallel to the centerline of County Road 110 and the South line of the Southeast Quarter of Section 14, a distance of 247.66' to an iron pin found; thence S.01°18'31"W. a distance of 672.04 feet to a Mag Nail found, passing thru an iron pin found at 647.04 feet in the North right—of—way line of County Road 110; The following described tract of land is part of the Southwest and Southeast Quarters of Section 14, Town 6 South, Range 6 East, Pusheta Township, Auglaize County, Ohio and is more particularly described as follows: Section 14 The PLACE OF BEGINNING is at a Monument Box found at the Southeast corner of the Southwest Quarter of Section 14, Pusheta Township and in the centerline of County Road 110, SITE thence N.89'52'04"W. along the centerline of County Road 110 and the South line of the Southeast Quarter of Section 14, a distance of 245.31 feet to the Mag Nail which was the true PLACE OF BEGINNING. thence N.89°57'22"W. along the centerline of County Road 110, a distance of 1,602.38 feet to a Mag Nail found in the intersection of County Road 110 and County Road 173, (Shelby— Containing in all 3.802 Acre of which 0.141 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, a R.R. Spike found; thence N.51°45'22"E. a distance of 300.00 feet to an iron pin found, passing thru an iron A. Heuker pin found at 25.00 feet in the North right—of—way line of County Road 173; thence N.23°58'57"W. a distance of 645.03 feet to an iron pin found; thence N.11°40'42"E. a distance of 113.24 feet to an iron pin found; thence N.88°37'45"W. a distance of 584.87 feet to a Mag Nail found, passing thru an iron pin found at 559.87 feet in the East right—of—way line of County Road 171; thence N.00°31'04"E. along the centerline of County Road 171, a distance of 60.00 feet to restrictions, and reservations, if any, of record or in use on said premises. Previous deed reference: Volume OR 527, page 362. This plat is on file in the Auglaize Deed Vol. OR 508. Pusheta Township, County Engineer's Office. This plat and description was prepared from an actual field survey performed by me, John W. Jauert, Professional Surveyor, Ohio No. 6920 in May, 2009. — Page 641. T-6-S, R-6-E, Auglaize County, Ohio. G. & J. Brag Deed Vol. OR 322, Page 731. a Mag Nail set; thence S.89°48'28"E. a distance of 164.98 feet to an iron pin set, passing thru an iron pin set for reference at 25.00 feet in the East right—of—way line of County Road 171; thence N.00°31'04"E., parallel to the centerline of County Road 171, a distance of 212.85 ZL N.89°49'41"W R. & D. Hickman TRACT ONE Deed Vol. OR 150, feet to an iron pin found; thence N.89°49'41"W. a distance of 164.98 feet to a Mag Nail found, passing thru an iron pin found at 25.00 feet in the East right—of—way line of County Road 171; thence N.00°31'04"E. along the centerline of County Road 171, a distance of 186.12 feet to Page 950. 259.308 ACRES (2.065 AC. R/W) I-448a Mag Nail found; thence S.87*43'56"E. a distance of 209.22 feet to an iron pin found, passing thru an iron 164.98' S 89°48'28"E. 127.220 ACRES S.E. 1/4 (0.605 AC. R/W) 132.088 ACRES S.W. 1/4 (1.460 AC. R/W) thence N.00°31'04"E., parallel to the centerline of County Road 171, a distance of 313.95 feet to an iron pin found; thence S.89*53'46"E. along the North line of the Southwest Quarter of said Section 14, a N.89°52'04"W. J. & A. Zwiebel Deed Vol. OR 527, Page 362. distance of 2,435.61 feet to a point; thence S.89°50'26"E. along the North line of the Southeast Quarter of Section 14, a distance of 2,644.30 feet to an iron pin set; thence S.00°32'00"W. along the East line of the Southeast Quarter of Section 14, a distance of 2,649.27 feet to a Monument Box at the Southeast corner of the Southeast Quarter of 596.01 J. & A. Zwiebel S.88°06'20"W. 325.22' Ref. Pin Found 6' west of corne Deed Vol. OR 527, Page 362. M-552 & 0-241 (295.61') Section 14, Pusheta Township; thence N.89°52'04"W. along the centerline of County Road 110 and the South line of the Southeast Quarter of Section 14, a distance of 683.44 feet to a Mag Nail found; thence N.03°59'22"E. a distance of 1,289.54 feet to an iron pin found, passing thru an iron pin found at 26.06 feet in the North right—of—way line of County Road 110; thence S.88°06'20"W. a distance of 325.22 feet to an iron pin found; thence S.01°33'29"W. a distance of 794.61 feet to an iron pin found; thence N.89°37'32"W. a distance of 378.42 feet to an iron pin found; thence N.89°37'04"W. parallel to the centerline of County Road 110, a distance of 550.28 2315, 1023. ?769 J. Metzge OR 539, OR 569, 30 & Q-1 thence N.89°52'04"W., parallel to the centerline of County Road 110, a distance of 550.28 S.A. Manger Deed Vol. OR 543, Page 1151. E-132 & G-122 feet to an iron pin found; thence N.01°18'31"E. a distance of 177.19 feet to an iron pin found; thence S.89°52'04"E., parallel to the centerline of County Road 110, a distance of 196.20 feet to an iron pin found, passing thru an iron pin found at 146.19 feet; thence N.01°18'31"E. a distance of 618.20 feet to an iron pin found; Pg. Pg. Pg. thence N.01-18 31 E. a distance of 618.20 feet to an Iron pin found; thence N.89*52'04"W., parallel to the centerline of County Road 110, a distance of 596.01 feet to an iron pin found, passing thru iron pins found at 50.01 feet and 296.20 feet; thence S.01*06'31"W. a distance of 1,290.16 feet to a Mag Nail found, passing thru an iron pin found at 1,265.16 feet in the North right—of—way line of County Road 110; thence N.89*52'04"W. along the centerline of County Road 110, a distance of 371.33 feet to the Monument Box which was the true PLACE OF BEGINNING. & F. Samme Merschman Deed Vol. OR Page 402. ROAD S.89°52'04"E S.89°52'04"E 247.66' 12.40' Containing in all 259.308 Acres of which 2.065 acre has been dedicated for highway purposes. 127.220 Acres is located in the Southeast Quarter of Section 14 and 132.088 Acres is located in the Southwest Quarter of Section 14, Pusheta Township. The above described tract of land is subject Deed Deed $A-\epsilon$ N.00°11'56"E. 196.20 to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous Deed Reference: Volume OR 527, page 362. This plat is on file in the Auglaize County Engineer's Office, PUS-14-3. TRACTTWOJ. & A. Zwiebel Deed Vol. OR 527, Page 362. N.89°37'32"W. 3.802 ACRES 0.141 ACRE R/W R. & T. Kantner Deed Vol. OR 78, D. & C. Jeanneret S.E. Corner, S.W. Quarter, — Deed Vol. OR 464, Page 392. Page 441. S.E. Corner, Section 14 S.W. Corner, H-698 & L-51 A-64 & A-67-S.E. Quarter, -S.W. Quarter, Section 14 Section 14 G Fryburg East Road (C.R. 110) 50' R/W N.89°52'04"W South Line of the Southwest Quarter of Section 14 50.00' N.89°52'04"W LEGEND JAUERT Iron Pin Set Iron Pin Found 6920 Mag Nail Set Basis of bearings is per the Auglaize Mag or PK Nail Found County Global Positioning System. Stone Found Jauert 11584 Monroe Road Wapakoneta, Ohio R. R. Spike Found

Monument Box Found

This Plat is on File in the Auglaize

County Engineer's Office - PUS-14-3

SHEET 1 OF 2

Professional Surveyor No. 6920

surveying

OUNTY: Auglaize TOWNSHIP: Pusheta SEC. 14

DATE: June 2009

LIENT: Anne Zwiebel

(419) 657-6999

(T-6-S; R-6-E)

SCALE: 1"=150' DWG.# 09-3539