229-04


40

-10-

Ó

msh

ahl Φ ai. O SW



Danny Fleshman D.V. 467, Pg. 1972 P.O.B N.1°-09'-20"E. N.87°-55'-14"E., 598.50' 120.12' Elanie M. Dahl Total 27.307 acres D.V. 315, Pg. 0142 N.89'-39'-06"W., 818.11' − N.45'-05'-31"W. Robert & Dorothea Rhoades (Trestees) 289.04 89.80' D.V. 481, Pg. 1504

© US Rt. 33

N.0°-15'-38"E.

206.10

S.89'-08'-51"W. 385.39

Auglaize County Historic Society D.V. 262,Pg. 119

LEGEND

A - Set #5 rebar B - Set Mag nail

corner post

corner post

1429.01

S.0°-01'-01"E.

ST. Johns Village

Cemetery

Being a parcel of land in the SW1/4 & SE1/4 of Section 32, T5S, R7E, Union Township, and being part of Outlot 33 in the Village of St. Johns, Auglaize County, Ohio, more particularly described as

Commencing for reference at an existing RR spike at the northwest corner of the E1/2 of the SW¼ of Section 32, thence S.0°-01'-01"E. (assumed bearing), 1429.01' to a set Mag nail at the POINT OF BEGINNING of the parcel to be described, thence the following courses;

- 1. N.87°-55'-14"E., 598.50' to a set #5 rebar, passing over a set #5 rebar at 55.04';
- 3. N.87°-55'-12"E., 936.83' to an existing 10" diam. wood corner post on the west R/W line of the Indiana - Ohio Railroad;

4. S.0°-01'-09"E. on said west line, 672.70' to a set #5 rebar;

- 5. N.89*-39'-06"W. on the north line of Outlot 34 and Outlot 33, 818.11' to a 2" diam. steel pipe corner post in concrete;
- 6. $5.0^{\circ}-52'-30"E.$, 517.43' to a set #5 rebar being N.0°-52'-30"W., 13.31' from a 91/4" x 4¼" I-beam post:
- 7. S.89°-08'-51"W. on the north line of Outlot 12 and Outlot 11, 385.39' to a set #5 rebar on the east line of the cemetery;
- 8. N.0°-15'-38"E. along a fence, 206.10' to an existing angle iron fence corner post;

9. N.45°-05'-31"W. along a fence, 89.80' to an existing angle iron fence post;

- 10. N.74°-31'-35"W. along a fence and the extension thereof, 289.04' to a set Mag nail on the centerline of S.R. 65, passing over an existing 3" diam. steel fence corner post at
- 11. N.0°-01'-01"W. on the centerline of S.R. 65, 668.41' to the PQINT OF BEGINNING.

The above—described parcel contains 27.307 acre, more or less, subject to all legal highways and easements of record at the time of survey.

This plat and description is based on a field survey on 6-6-04 by, Bacon & Associates, LLC under the direction of Clayton T. Bacon, P.S. #6179.

~ 3601.45'

CLAYTO BACON

1127+42.85

S.89°-08'-51"W.

This description and plat is based on an actual field survey performed on 6-6-04 , by Bacon & Associates under the the direction of Clayton T. Bacon, P.S. #6179