

BEING PT. OF THE S/W 1/4 OF SEC. 29 WASHINGTON TWP.
T-6-S--R-5-E AUGLAIZE COUNTY OHIO


N/W Cor.
S/W 1/4

N 89° 18' 20" W

ALL BEARINGS HEREON
ARE CORRELATED TO THE
STATE OF OHIO CENTER
LINE SURVEY OF S.R.#29

A 2x2 grid with a black rectangle in the bottom-left cell.

Washington Twp.
Section 29
T-6-S--R-5-E
Auglaize, Co. OHIO



Scale: 1"=200'

SR# 219

RR SPIKE (ODOT)

CENTER of SEC. 29
ESTABLISHED BY
MEANS of Double
PRORATION WITH
REFERENCE TO
1877 SURVEY,
DIFFER FROM COR.
AS SET BY C.H.S.

0" STEEL
COR. POST
Y CONC.
COR. STONE

2673.09

✓ 01° 19' 20" E

N 01° 22' 10" E

N 01° 25' 00" E

North-south Half Section
N 01° 27' 50" E 2674.27

Southland
S 89° 16' 25" E

$\frac{660.62'}{2642.48}$
 South Line of section
 Survey

SURVEY BY THOMAS W. STEINKE # 6177
BOTKINS, OHIO

SCALE: 1" = 200'	APPROVED BY
DATE: 3-26-81	

DRAWING NUMBER
81-1067