	\$ 1.37217	ME
Starting Bearing	E4 -	32
R.R. SPIKE SET OVER NAIL FOUND	PK HAIL SET	VORREPIKE -N-
N89° 00'E	10 50' R/W	MODELND 7
666.28	1944/1 2 2003 90	Scale: 1 = 200
SQUARE		20 V
\$ 89°00' W	15 N	
169°32'30 3°P 5. 255 ACRES 3"/	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	007
o o	no SECTION 31 NWA	C
U m		P Roan
wood n	RANGE SE LOGAN TWP.	Loop
1.P. SET. 350.00	DUGLAIZE CO.	
589°00'W	0410	
(15.0)		VICINITY
Being 5.255 Acres in the north west quar	rter of Section 31. Town 4 S.	MAP Range 5 E,
Logan Township, Auglaize County, Ohio as		
Commencing at the center line intersect	1 **** #	
the Loop Road number 206-A, also being t		orth west
quarter of the north east quarter of Se	etion 31.	
Thence South 89° 00' West, 2003.90 feet		
center line of the National Road to a P	.K. nail set in the center of	a bridge(no. 310
and being the place of beginning for th	e tract of land herein descri	bed;
Thence South 27° 16' West, 150.60 feet	to a point, reference pin set	South 89° 001
West, 27.00 feet.		
Thence South 37° 43' 30" West, 393.83 f	eet to a point, reference 8"	wood post
South 89° 00' West, 15.00 feet.		
<u> </u>	•	<i>*</i>
Thence South 89° 00' West, 350.00 feet	to an iron pin.	nal Road.
Thence South 89° 00' West, 350.00 feet Thence North 0° 49' West to a railroad	to an iron pin.  Spike in the center of Nation	
Thence South 89° 00' West, 350.00 feet  Thence North 0° 49' West to a railroad  Thence North 89° 00' East with the nort	to an iron pin.  Spike in the center of Nation the line of Section 31,666.28 in the line of Section 31,666.20 in the line of Section	eet to the
Thence South 89° 00' West, 350.00 feet  Thence North 0° 49' West to a railroad  Thence North 89° 00' East with the nort  point of beginning. Containing 5.255	to an iron pin.  Spike in the center of Nation th line of Section 31,666.28 in the line and being subject to all	Teet to the
Thence South 89° 00' West, 350.00 feet Thence North 0° 49' West to a railroad Thence North 89° 00' East with the nort	to an iron pin.  Spike in the center of Nation the line of Section 31,666.28 in the line of Section 31,666.20 in the line of Section	Teet to the
Thence South 89° 00' West, 350.00 feet  Thence North 0° 49' West to a railroad  Thence North 89° 00' East with the nort  point of beginning. Containing 5.255 A	to an iron pin.  Spike in the center of Nation the line of Section 31,666.28 in the line and being subject to all thomas	Jeet to the
Thence South 89° 00' West, 350.00 feet Thence North 0° 49' West to a railroad Thence North 89° 00' East with the nort point of beginning. Containing 5.255 feesements and rights-of-way of record.  Survey and description prepared by	to an iron pin.  Spike in the center of Nation the line of Section 31,666.28 in the line of Section	Seet to the legal  Stanke  For No. S - 6177
Thence South 89° 00' West, 350.00 feet  Thence North 0° 49' West to a railroad  Thence North 89° 00' East with the nort  point of beginning. Containing 5.255 feesements and rights—of—way of record.  Survey and description prepared by  Signature by a representative of the County Engineer's Dept.  Hence South 89° 00' West, 350.00 feet	to an iron pin.  Spike in the center of Nation the line of Section 31,666.28 in the line and being subject to all thomas W. Steinke Reg. Survey	Teet to the  legal  Lance  yor No. S - 6177  County Commissioner(s)
Thence South 89° 00' West, 350.00 feet  Thence North 0° 49' West to a railroad  Thence North 89° 00' East with the nort  point of beginning. Containing 5.255 feetsements and rights—of—way of record.  Survey and description prepared by  Signature by a representative of the County Engineer's Dept.  denotes that this plat meets tax map plat requirements.	to an iron pin.  Spike in the center of Nation the line of Section 31,666.28 in the line of Section	Teet to the  legal  Lance  yor No. S - 6177  County Commissioner(s)
Thence South 89° 00' West, 350.00 feet  Thence North 0° 49' West to a railroad  Thence North 89° 00' East with the nort  point of beginning. Containing 5.255 feetsements and rights—of—way of record.  Survey and description prepared by  Signature by a representative of the County Engineer's Dept.  denotes that this plat meets tax map plat requirements.  Date  Signature by a representative of the County Health Dept.	to an iron pin.  Spike in the center of Nation the line of Section 31,666.28 in the line of Section	Ceet to the  Ligal  Linke  For No. S - 6177  County Commissioner(s)  Date  Auglaize County Regional
Thence South 89° 00' West, 350.00 feet  Thence North 0° 49' West to a railroad  Thence North 89° 00' East with the nort  point of beginning. Containing 5.255 A  easements and rights—of—way of record.  Survey and description prepared by  Signature by a representative of the County Engineer's Dept.  denotes that this plat meets tax map plat requirements.  Signed:  Date  Signature by a representative of the County Health Dept.	to an iron pin.  Spike in the center of Nation the line of Section 31,666.28 in the line of Section	Ceet to the  Ligal  Linke  For No. S - 6177  County Commissioner(s)  Date  Auglaize County Regional al of this plat.
Thence South 89° 00' West, 350.00 feet Thence North 0° 49' West to a railroad Thence North 89° 00' East with the nort point of beginning. Containing 5.255 feetsements and rights—of—way of record.  Survey and description prepared by Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed:  Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed:  Date  Date	to an iron pin.  Spike in the center of Nation the line of Section 31,666.28 in the line of Section	Ceet to the  I legal  Lande  For No. S - 6177  County Commissioner(s)  Date  Auglaize County Regional al of his plat.  Date
Thence South 89° 00' West, 350.00 feet  Thence North 0° 49' West to a railroad  Thence North 89° 00' East with the nort  point of beginning. Containing 5.255 feetsements and rights-of-way of record.  Survey and description prepared by  Signature by a representative of the County Engineer's Dept.  denotes that this plat meets tax map plat requirements.  Signed:  Date  THOMAS W. STEINKE LAND SURVEYING  Client County Client County Client County Client County Client County Client County Coun	to an iron pin.  Spike in the center of Nation the line of Section 31,666.28 in the line of Section	Ceet to the  legal  Lande  For No. S - 6177  County Commissioner(s)  Date  Auglaize County Regional al of this plat.  Date  eta, Ohio 45895  Sec. 31 N.W.
Thence South 89° 00' West, 350.00 feet  Thence North 0° 49' West to a railroad  Thence North 89° 00' East with the nort  point of beginning. Containing 5.255 feetsements and rights—of—way of record.  Survey and description prepared by  Signature by a representative of the County Engineer's Dept.  denotes that this plat meets tax map plat requirements.  Signed:  Date  THOMAS W. STEINKE  LAND SURVEYING  BOTKINS, OHIO  Checked b.  Checked b.	to an iron pin.  Spike in the center of Nation the line of Section 31,666.28 in the line of Section	Ceet to the  legal  Lande  For No. S - 6177  County Commissioner(s)  Date  Auglaize County Regional al of his plat.  Date  Date  Sta. Ohio 45895