

LEGEND


- "A" = RAILROAD SPIKE OVER STONE @ THE N. 1/4 POINT OF SEC. 36 (SEE CO. ENGR'S RECORDS)
- "B" = STONE FD. @ N.E. COR. OF SEC. 36
- "C" = RAILROAD SPIKE SET
- "D" = 5/8 INCH IRON BAR SET.

THE NORTH LINE OF SEC. 36 WAS ASSUMED TO BEAR EAST. ALL OTHER BEARINGS WERE CALCULATED FROM ANGLES TURNED.

N. LINE OF SEC. 36 & E. VOGEL RD. (50')




LOCATION SKETCH



SEC. 36 NOBLE TOWNSHIP

THIS SURVEY



SURVEYED BY Gordon L. Geeslin
GORDON L. GEESLIN
REGISTERED SURVEYOR
5372

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a representative of the County Commissioner(s) denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

GORDON L. GEESLIN
REG. SURVEYOR 5372

Client NOAH CLAUSING
County AUGLAIZE Twp. NOBLE Sec. 36
Drawn by G.G. Scale 1" = 50' Drwg. No. _____
Checked by GG Date 11 JULY 74
Sheet 1 of 2

53

53

(T. 5 S., R. 4 E.)

July 11, 1974

SURVEY DESCRIPTION

Scale:

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the north half of the northeast quarter of Section 36, Town 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at a railroad spike over the corner stone at the north quarter point of said Section 36-

Thence, east, along the north line of the northeast quarter of said Section 36 and the centerline of Vogel Road, a distance of three hundred seventy and 42/100 (370.42) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing east, along the last described line, a distance of one hundred seventy-five (175.00) feet to a railroad spike-

Thence, south 00°32' west, a distance of two hundred forty-eight and 92/100 (248.92) feet to a 5/8 inch iron bar-

Thence, west, a distance of one hundred seventy-five (175.00) feet to a 5/8 inch iron bar-

Thence, north 00°32' east, a distance of two hundred forty-eight and 92/100 (248.92) feet to the place of beginning.

Containing 1.000 acre of land more or less

Subject to 0.100 acre in road right-of-way and all other easements and right-of-way of record.

The north line of the northeast quarter of Section 36 was assumed to bear east-west. All other bearings were calculated from angles turned.

This tract is a part of Noah Clausling's present 76.6 acre tract as recorded in deed volume 147, page 500.



Surveyed by:

Gordon L. Geeslin
Gordon L. Geeslin
Registered Surveyor 5372

to St Marys City for approval

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

GORDON L. GEESLIN
REG. SURVEYOR
54 5372

Client NOAH CLAUSING
County AUGLAIZE Twp. NOBLE Sec. 36
Drawn by G.G. Scale _____ Drwg. No. _____
Checked by GG Date 11 JULY '74
Sheet 2 of 2 54 (T 5 S; R 4 E)