


436.46

90°00' 90°00'

Series

1" = 100'



N

411.09

5.613 Ac.

GRAIN & FERTILIZER
BUILDINGS

BUILDING

175.00

TURN AROUND
EASEMENT

1.000 Ac.

EXIST.
HOUSE

248.91

270°00'

15' EASEMENT
FOR INGRESS &
EGRESS

Silos



660.00

SECTION LINE

175.00


175.00

261.46

60' R/W

N.W. COR
SEC 22

PEPPLE ROAD
SECTION LINE




SECTION 22 (N.W. 1/4)
TOWN 5 S
RANGE 8 E
WAYNE TWP.
AUGLAIZE CO.

LEGEND

IRON PIN

R.R. SPKE



S-6177

Thomas W. Steinke, SURVEYOR NO. S - 6177

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.

Signed: _____ Date: _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.

Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.

Signed: _____ Date: _____

THOMAS W. STEINKE
LAND SURVEYING
DETROIT, OHIO
45306



Client: John Cassinelli, P.O. Box 160, Springfield, Ohio 45503
County: Auglaize
Drawing No.: 9-100
Scale: 1" = 100' Drawing No. 9-100
Sheet No.: 1 of 1 Date: Sept. 1974
Title: S. R. 100

96

96

DESCRIPTION OF 5.613 ACRE TRACT



Scale:

Being 5.613 Acres in the north west quarter of Section 22, Town 5 S, Range 8 E, Wayne Township, Auglaize County, Ohio and being further described as follows:

Commencing at the north west corner of Section 22 Thence east with the center line of State Route # 67 and the north line of Section 22, 369.45 feet to a railroad spike and the place of beginning for the tract of land herein described:

Thence continuing east with the center line of State Route # 67, 261.16 feet to a railroad spike.

Thence south with an interior angle of $90^{\circ} 00'$, 248.91 feet to a point.

Thence east with an interior angle of $270^{\circ} 00'$, 175.00 feet to an iron pin.

Thence south with an interior angle of $90^{\circ} 00'$, 411.09 feet to an iron pin.

Thence west with an interior angle of $90^{\circ} 00'$, 436.46 feet to an iron pin.

Thence north with an interior angle of $90^{\circ} 00'$, 660.00 feet to a railroad spike and point of beginning. Containing 5.613 Acres and subject to all legal easements and rights-of-way of record. State Route # 67 being a 60' total right-of-way and iron pins set on the property lines at the south right-of-way line.

Subject to a fifteen ft. (15') ingress and egress easement, 15' west and parallel to the line herein described. Beginning at the north west corner of Section 22, Thence east with the centerline of State Route # 67, 630.91 feet to a railroad spike and point of beginning.

Thence South with an angle of $90^{\circ} 00'$ 248.91 feet to a point.

This easement to serve as access to the property containing 1.000 Acres, which was divided from the Cummings Griffin Company, Inc.

Thomas W. Steinke



Description and Survey prepared by Thomas W. Steinke reg. surveyor No. S - 6177

Signature by a representative of the County Engineer's Dept. denotes compliance with tax map plat requirements.
Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s) denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Drawn by _____ Date: _____
County: Auglaize Twp.: Wayne Sec.: 22
Scale: _____ Drwg. No. _____
Checked by _____ Date: _____
Sheet: 2 of 2 (T.S.R.)

97

97

DESCRIPTION OF 1,000 ACRE TRACT

Being 1,000 Acres in the north west quarter of Section 22, Town 5 S,
Range 8 E, Wayne Township, Auglaize County, Ohio and being further
described as follows:

Commencing at the north west corner of Section 22, Thence east with the
centerline of State Route # 67 and the north line of Section 22, 630.91
feet to a railroad spike and the place of beginning for the tract of land
herein described.

Thence continuing east with the center line of State Route # 67, 175.00
feet to a railroad spike.

Thence south with an interior angle of $90^{\circ} 00'$, 248.91 feet to an iron pin.

Thence west with an interior angle of $90^{\circ} 00'$, 175.00 feet to a point.

Thence north with an interior angle of $90^{\circ} 00'$, 248.91 feet to a railroad
spike and place of beginning. Containing 1,000 Acres and subject to all
legal easements and rights-of-way of record. State Route # 67 being a
60' total right-of-way and iron pins set on the property lines at the
south right-of-way line.

Subject to a turn-around easement at the south west corner of the tract
herein described. Said easement being further described as follows,

Commencing at the north west corner of Section 22, Thence east with the center
line of State Route # 67, 630.91 feet to a railroad spike.

Thence south with a angle of $90^{\circ} 00'$, 248.91 feet to a point and place of
beginning.

Thence east with the north property line of the above mentioned 1,000 Acre
tract 60.00 feet

Thence north-west 84.85 feet to a point on the west line of said 1,000 Acre
Tract.

Thence south with the west property line 60.00 feet to the place of
beginning.

Thomas W. Stainke

Survey and description prepared by Thomas W. Stainke reg. surveyor no. # 6177

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of the County Health Dept.
denotes agreement with Health Department
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Board of
Planning Commissioners denotes approval of this plat
Signed: _____ Date: _____

Plat No. 1000-Acre Tract
County of Auglaize, State of Ohio
Drawn by _____ Sent to _____ Drawn No. _____
Checked by _____ Date _____
Sheet 1 of 1 Total _____ (1) C.R. 194