

Being part of the North West quarter of Section 21, Town 5 S, Range 8 E, Wayne Township, Augleise County, Ohio, and being further described as follows:

Gommencing at an iron pin at the North West corner of Section 21 also being the center line intersection of State Route # 67 and State Route # 196.

Thence South with the center line of S.R. # 196, 1444.67 feet to a railroad spike and place of beginning.

Thence eastward with an interior angle of 89° 50', distance of 212.49 feet to an iron pin. Thence westward with an interior angle of 89° 50', distance of 410.00 feet to an iron pin. Thence westward with an interior angle of 89° 50', distance of 212.49 feet to a railroad spike in the center line of State Route # 196.

Thence northward with an interior of 90° 10' with the center line of State Route # 196, distance of 410.00 feet to a railroad spike and place of beginning. Iron pins being set on the property lines on the eastern right—of—way of S.R.#196. Centerline of S.R. # 196 has a Bearing of North 1° 03' East, and being a sixty ft. right—of—way road.

Containing 2.000 Acres and being subject to all legal easements and rights—of—way of record



Thomas W Strike

Survey and Description prepared by Thamas W. Steinke

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date	Signature by a (representative of the) County Commissioner(s) denotes approval of this plat. Signed: Date	
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: Date	
LAND SURVEYING Drawn by_ BOTKINS OHIO Checked by	Client Joseph Pepple RR# WAYNESFIELD NOMO 15896 County AUGLAIZE Twp. WAYNE Sec. 21 NW44 Drawn by Jup Scale 1"5 100 Drwg. No. 74-49 Checked by Jup Date August 27, 1974 Sheet 1 of 1 (T 5 8; R 8 E)	