

N

W. LINE OF N.W. 1/4 OF SEC. 21 & TRI-TWP. RD. (40

N. 00° 30' E ~ 397.50' BEARING ASSUMED

"C"

N. 89° 37' W. ~ 547.92'

208.71'

"D"

339.21'

"F"

834.84'

"B"

"A" = IRON BAR @ N.W. COR. SEC. 21

"B" = RAILROAD SPIKE @ W. 1/4 PT. SEC. 21

"C" = " " " FD. @ N.W. COR. TRACT 4 OF PREVIOUS DAMMEYER SURVEY.


"D" = IRON BAR @ N.E. COR. OF PREV. SURVEY.

"E" = RAILROAD SPIKE SET.

"F" = 5/8" IRON BAR SET.

5.000 ACRES

LEGND



LOCATION SKETCH

LOUIS DAMMEYER SURVEY ~ PART OF SECTION 21, TOWN 6 SOUTH, RANGE 4 EAST, (ST. MARYS TWP.), AUGLAIZE COUNTY, OHIO.

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s) denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

GORDON L. GEESLIN
REGISTERED SURVEYOR
ST. MARYS, OHIO 45885

Client LOUIS DAMMEYER
County AUGLAIZE Twp. ST. MARYS Sec. 21
Drawn by GG Scale 1" = 100' Draw. No. _____
Checked by " Date 20 DEC. 1974
Sheet 1 of 2 (T & S: H + B)

December 20, 1974



Scale:

SURVEY DESCRIPTION

Being a parcel of land situated in St. Marys Township, Auglaize County, Ohio, in the northwest quarter of Section 21, Township 6 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at a railroad spike at the west quarter point of said Section 21-

Thence, north 00°30' east along the west line of the northwest quarter of said Section 21 and the centerline of Tri-Township Road, a distance of eight hundred thirty-four and 84/100 (834.84) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing north 00°30' east along the last described line, a distance of three hundred ninety-seven and 50/100 (397.50) feet to a railroad spike-

Thence, south 89°37' east, a distance of five hundred forty-seven and 92/100 (547.92) feet to a 5/8 inch iron bar-

Thence, south 00°30' west, a distance of three hundred ninety-seven and 50/100 (397.50) feet to a 5/8 inch iron bar-

Thence, north 89°37' west, a distance of five hundred forty-seven and 92/100 (547.92) feet to the place of beginning.

Containing 5.000 acres of land more or less.

Subject to all easements and right-of-way of record.

The west line of the northwest quarter of Section 21 was assumed to bear north 00°30' east. All other bearings were calculated from angles turned.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin
Registered Surveyor 5372



Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

GORDON L. GEESLIN
REGISTERED SURVEYOR
ST. MARYS, OHIO.

Client LOUIS DAMMEYER
County AUGLAIZE Twp. ST. MARYS Sec. 21
Drawn by _____ Scale _____ Drwg. No. _____
Checked by _____ Date _____
Sheet 2 of 3 (T 6 S R 4 E)

SURVEY DESCRIPTION

Being a parcel of land situated in St. Marys Township, Auglaize County, Ohio, in the northwest quarter of Section 21, Township 6 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at a railroad spike at the west quarter point of said Section 21-

Thence, north $00^{\circ}30'$ East along the west line of the northwest quarter of said Section 21 and the centerline of Tri-Township Road, a distance of eight hundred thirty-four and $84/100$ (834.84) feet to a railroad spike-

Thence, south $89^{\circ}37'$ east, a distance of two hundred eight and $71/100$ (208.71) feet to an iron bar. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing south $89^{\circ}37'$ east, a distance of three hundred thirty-nine and $21/100$ (339.21) feet to a $5/8$ inch iron bar-

Thence, north $00^{\circ}30'$ east, a distance of three hundred ninety-seven and $50/100$ (397.50) feet to a $5/8$ inch iron bar-

Thence, north $89^{\circ}37'$ west, a distance of three hundred thirty-nine and $21/100$ (339.21) feet to a $5/8$ inch iron bar-

Thence, south $00^{\circ}30'$ west, a distance of three hundred ninety-seven and $50/100$ (397.50) feet to the place of beginning.

Containing 3.095 acres of land more or less.

Subject to all easements and right-of-way of record.

The west line of the northwest quarter of Section 21 was assumed to bear north $00^{\circ}30'$ east. All other bearings were calculated from angles turned.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin
Registered Surveyor 5372



Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

GORDON L. GEESLIN
REGISTERED SURVEYOR
ST. MARYS, OHIO.

Client LOUIS DAMMEYER
County AUGLAIZE Twp. ST. MARYS Sec. 21
Drawn by _____ Scale _____ Dwg. No. _____
Checked by _____ Date _____
Sheet 3 of 3 (T 6 S 1 R 4 E)