



SURVEY FOR THE PURPOSE OF DEVIDING
PARCEL RECORDED IN DEED VOLUME 153, PG. 395,
LOCATED IN THE W. 1/2 OF SECTION 29, TOWN
6 SOUTH, RANGE 5 EAST (WASHINGTON TWP),
AUGLAIZE COUNTY, OHIO.

NOVEMBER 1974 SCALE 1"=100'

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: _____ Date: _____	Signature by a (representative of the) County Commissioner(s) denotes approval of this plat. Signed: _____ Date: _____
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: _____ Date: _____	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: _____ Date: _____
GORDON L. GEESLIN REG. SURVEYOR ST. MARYS, OHIO	Client <u>LYNN HERSHFIELD</u> County <u>AUGLAIZE</u> Twp. <u>WASHINGTON</u> <u>29</u> Drawn by <u>GG</u> Scale <u>1"=100'</u> Drwg. No. _____ Checked by <u>"</u> Date <u>11-4-74</u> Sheet <u>1</u> of <u>2</u> (T 6 S R 5 E)

Nov. 4, 1974



SURVEY DESCRIPTION

Being a parcel of land situated in Washington Township, Auglaize County, Ohio, in the west half of Section 29, Township 6 South, Range 5 East. Being more particularly described as follows:

Scale: _____

Beginning at a railroad spike at the southwest corner of a 1.21 acre tract of land conveyed to Dale F. and Evelyn E. Grimes by deed recorded in deed volume 151, page 196. Said point being in the centerline of the Botkins Angle Road, four thousand and 70/100 (4000.70) feet northwesterly from the intersection of said centerline of Botkins Angle Road with the east line of Section 29-

Thence, north $83^{\circ}35'13''$ west along the centerline of said Botkins Angle Road, a distance of seventy-four and 67/100 (74.67) feet to a railroad spike-

Thence, north $01^{\circ}40'$ east, a distance of two hundred forty-six and 34/100 (246.34) feet to a 5/8 inch iron bar in the south line of Robert H. Kuck's land-

Thence, south $68^{\circ}36'51''$ east along said Kuck's south line, a distance of seventy-seven and 86/100 (77.86) feet to a 5/8 inch iron bar at the northwest corner of the afore mentioned 1.21 acre tract-

Thence, south $01^{\circ}23'$ west along the west line of said 1.21 acre tract, a distance of two hundred twenty-six and 25/100 (226.25) feet to the place of beginning.

Containing 0.400 acre of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey by Gordon L. Geeslin, Registered Surveyor 5372, of this tract dated November 4, 1974, on file in the Auglaize County Engineer's Office, which is incorporated as a part of this description.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin
Registered Surveyor 5372



Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.

Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.

Signed: _____ Date _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.

Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.

Signed: _____ Date _____

GORDON L. GEESLIN
REG. SURVEYOR
ST. MARYS, OHIO.

Client LYNN HERSHFIELD
County AUGLAIZE Twp. WASHINGTON Sec. 29
Drawn by GG Scale _____ Drwg. No. _____
Checked by " Date 11-4-74
Sheet 2 of 2 (T 6 S; R 5 E)