

EAST LINE SEC. 32
V. S. LAMPERT RD

CHORDS FROM NORTH TO SOUTH

- 1) S. 01° 30' 45" W. ~ 30.00'
- 2) S. 01° 46' 45" W. ~ 30.00'
- 3) S. 02° 19' 33" W. ~ 30.00'
- 4) S. 03° 07' 33" W. ~ 30.00'
- 5) S. 04° 13' 11" W. ~ 0.63'



Scale:
1" = 60'

"G" S. 01° 27' 57" W.
1233.38'


131.88' "B"

"E"

95.13'

"A" 48.32'

N. 12° 16' 27" E. ~ 257.78'
RIGHT-OF-WAY LINE



LOCATION PLAN
SEC. 32
NODLE TWP.

2.000 ACRES

S. 69° 24' 23" E. ~ 328.19'

308.19'

330.60'

N. 89° 24' 23" W. ~ 476.19'

N. 64° 14' 17" E.
32.81'

6A

6A

"D"

N. 01° 24' 42" E.
237.90'

"C"

N. 05° 15' 52" W.
38.47'


N. 09° 45' E.
101.00'

N. 30° 50' E.
14.50'

"F"

¢ OF OPEN DITCH

N. 50° 55' E.
51.00'



LEGEND

- "A" = RAILROAD SPIKE F.D.
- "B" = "P.K." NAIL @ T.S. OF 300' SPIRAL OF 3° 00' CURVE W/ Δ ANGLE OF 58° 22' 35" N. 81° 10' E. 57.00'
- "C" = TACKED HUB SET.
- "D" = IRON PIPE F.D.
- "E" = RAILROAD SPIKE SET.
- "F" = 5/8 INCH IRON BAR SET.
- "G" = CORNER STONE @ N.E. COR SEC. 32. 38.05'

NOTE: THE EAST LINE SEC. 32 ASSUMED TO BEAR N. 01° 27' 57" E.

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

6A
GORDON L. GEESLIN
REGISTERED SURVEYOR
5372

Client VIRGIN LAMPERT Twp. NODLE Sec. 32
County AUGLAIZE Scale 1" = 60' Drawn by GG
Checked by GG Date 6-12-77
Sheet 1 of 1

199

199

6A

June 12, 1974

SURVEY DESCRIPTION (Tract "A")

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the east half of the northeast quarter of Section 32, Town 5 South, Range 4 East. Being more particularly described as follows:

Scale: _____

Commencing for reference at a cornerstone at the northeast corner of said Section 32. Said point also being the northeast corner of John Tobin's Subdivision as recorded in Plat Book "B", Page 23 and on the centerline of Lampert Road-

Thence, south $1^{\circ}27'57''$ west, along the east line of Section 32 and the centerline of Lampert Road, a distance of one thousand two hundred thirty-three and $88/100$ (1233.88) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing south $01^{\circ}27'57''$ west, along the last described line, a distance of one hundred thirty-one and $88/100$ (131.88) feet to a "P.K." nail at the T.S. of a 300.00 foot spiral curve of a $9^{\circ}00'$ curve to the right having a delta angle of $58^{\circ}22'35''$ -

Thence, along chords of said spiral the following courses and distances: south $01^{\circ}30'45''$ west, 30.00 feet; south $01^{\circ}46'45''$ west, 30.00 feet; south $02^{\circ}19'33''$ west, 30.00 feet; south $03^{\circ}07'33''$ west, 30.00 feet; south $04^{\circ}13'11''$ west, 0.63 feet to a railroad spike-

Thence, north $89^{\circ}24'23''$ west, a distance of four hundred seventy-six and $19/100$ (476.19) feet to the center of an open ditch. Said line passing through a $5/8$ inch iron bar at three hundred thirty and $60/100$ (330.60) feet-


Thence, along the center of said open ditch the following courses and distances: north $74^{\circ}05'$ east, 38.06 feet; north $81^{\circ}10'$ east, 57.00 feet; north $50^{\circ}55'$ east, 51.00 feet; north $30^{\circ}50'$ east, 16.50 feet; north $01^{\circ}45'$ east, 47.50 feet; north $09^{\circ}45'$ east, 101.00 feet; north $05^{\circ}15'52''$ west, 38.47 feet to a point-

Thence, leaving said centerline of ditch, south $89^{\circ}24'23''$ east, a distance of three hundred twenty-eight and $19/100$ (328.19) feet to the place of beginning.

Containing 2.000 acres of land more or less.

Subject to 0.198 acre in Lampert Road right-of-way and all other easements and right-of-way of record.

The east line of Section 32 was assumed to bear north $1^{\circ}27'57''$ east. All other bearings were calculated from angles turned.



Surveyed by Gordon L. Geeslin

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s) denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

GORDON L. GEESLIN
REG SURV. 5372

Client VIRGIL LAMPERT
County AUGLAIZE Twp. NOBLE Sec. 32
Drawn by G.G. Scale 1" = 60' Drwg. No. _____
Checked by G.G. Date 6-12-74
Sheet 1 of 2

(T. 5 S. R. 4 E.)

200

200

66