




Scale: 1"=60'

N

LOCATION SKETCH



SEC. 16
NOBLE TWP.

S. 01° 46' W.
272.25'

1.000
ACRE

N. 01° 46' E.
272.25'

N. 88° 30' W.
160.00'

SCALE 1"=60'

"A" 759.80' "C" S. 88° 30' E. 160.00' "C" 409.57' "B"
S. LINE OF SECTION 16 & E. NOBLE RD.

LEGEND

- "A" = STONE FD. @ S 1/4 PT. OF SEC. 16
- "B" = " " " SE. COR. OF W. 1/2 OF SEC. 16.
- "C" = HARBOR TOOTH SPIKE SET.
- "D" = 5/8" IRON BAR SET.



E. NOBLE RD.

SURVEYED BY Gordon L. Geeslin
GORDON L. GEESLIN
REGISTERED SURVEYOR 5372

SURVEY FOR WILLIAM POST IN THE W. 1/2 OF
THE SE. 1/4 OF SECTION 16, TOWN 5 SOUTH, RANGE
4 EAST (NOBLE TWP) AUGLAIZE COUNTY, OHIO.

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

GORDON L. GEESLIN
REGISTERED SURVEYOR
5372, OHIO

Client WILLIAM POST
County AUGLAIZE Twp. NOBLE Sec. 16
Drawn by G.L.G. Scale 1"=60' Drawn No. _____
Checked by G.L.G. Date APR 15 1975
Sheet 1 of 1

283

283

April 2, 1975



SURVEY DESCRIPTION

Scale: _____

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the west half of the southeast quarter of Section 16, Township 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at a corner stone at the south quarter point of said Section 16-

Thence, south $88^{\circ}30'$ east, along the south line of the southeast quarter of said Section 16 and the centerline of Noble Road, a distance of seven hundred fifty-nine and $80/100$ (759.80) feet to a harrow tooth spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing south $88^{\circ}30'$ east along the last described line, a distance of one hundred sixty (160.00) feet to a harrow tooth spike-

Thence north $01^{\circ}46'$ east, a distance of two hundred seventy-two and $25/100$ (272.25) feet to a $5/8$ inch iron bar-

Thence, north $88^{\circ}30'$ west, a distance of one hundred sixty (160.00) feet to a $5/8$ inch iron bar-

Thence, south $01^{\circ}46'$ west, a distance of two hundred seventy-two and $25/100$ (272.25) feet to the place of beginning.

Containing 1.000 acre of land more or less.


Subject to all easements and right-of-way of record.

The south line of the southeast quarter of Section 16 was assumed to bear south $88^{\circ}30'$ east. All other bearings were calculated from angles turned.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin
Registered Surveyor 5372



Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

GORDON L. GEESLIN
REGISTERED SURVEYOR
284

Client WILLIAM POST
County AUGLAIZE Twp. NOBLE Sec. 16
Drawn by _____ Scale _____ Date 2 APRIL 1975
Checked by _____ Sheet 2 of 2 284