



SURVEYED BY Gordon L. Geeslin
 GORDON L. GEESLIN
 REGISTERED SURVEYOR 5372

ZIEGENBUSCH SURVEY ~ PART OF THE
 SW 1/4 OF THE SE 1/4 OF SEC. 30, TOWN 5 SOUTH,
 RANGE 4 EAST (NOBLE TWP.), AUGLAIZE CO., OHIO.
 APRIL 1975 SCALE 1" = 200'

Accepted by a representative of the County Engineer's Dept.
 that this plat meets tax map plat requirements.
 Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s)
 denotes approval of this plat.
 Signed: _____ Date: _____

Accepted by a representative of the County Health Dept.
 that this plat meets health regulations.
 Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
 Planning Commission denotes approval of this plat.
 Signed: _____ Date: _____

GORDON L. GEESLIN
 REGISTERED SURVEYOR

Client RICHARD ZIEGENBUSCH
 County AUGLAIZE Twp. NOBLE Sec. 30
 Drawn by GG Scale 1" = 200' Drwg. No. _____
 Checked by _____ Date _____
 Signed 1 _____

324

324

(T 5, S 14 E)

SURVEY DESCRIPTION



Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the southwest quarter of the southeast quarter of Section 30, Township 5 South, Range 4 East. Being more particularly described as follows:

Scale: _____

Beginning at a one inch iron bar at the south quarter point of said Section 30-

Thence, north $02^{\circ}00'$ east, along the west line of the southeast quarter of said Section 30 and the centerline of Koenig Road, a distance of five hundred seventy-three and $30/100$ (573.30) feet to a railroad spike-

Thence, south $88^{\circ}12'13''$ east, a distance of one thousand three hundred thirty-three and $48/100$ (1333.48) feet to a $5/8$ inch iron bar on the east line of the southwest quarter of the southeast quarter of said Section 30-

Thence, south $01^{\circ}52'33''$ west, along said quarter-quarter line, a distance of five hundred seventy-seven and $04/100$ (577.04) feet to a corner post at the southeast corner of the southwest quarter of the southeast quarter of said Section 30-

Thence, north $88^{\circ}02'32''$ west, along the south line of the southeast quarter of said Section 30, a distance of one thousand three hundred thirty-four and $71/100$ (1334.71) feet to the place of beginning.

Containing 17.615 acres of land more or less.

Subject to all easements and right-of-way of record.

The west line of the southeast quarter of Section 30 was assumed to bear north $02^{\circ}00'$ east. All other bearings were calculated from angles turned.



Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin
Registered Surveyor 5372

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.

Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.

Signed: _____ Date: _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.

Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.

Signed: _____ Date: _____

GORDON L. GEESLIN

REGISTERED SURVEYOR

325 AUGLAIZE COUNTY, OHIO (5383)

Client RICHARD ZIEGENBUSCH

County AUGLAIZE Twp. NOBLE Sec. 30

Drawn by _____ Scale _____ Drawn No. _____

Checked by _____ Date 30 APRIL 1975

Sheet 2 of 2 325 (P. 5, 8, 11, 12)