

Thomas W. Steinke

Signature by a representative of the County Engineer's Dept.  
denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a (representative of the) County Commissioner(s)  
denotes approval of this plat.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the County Health Dept.  
denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the Auglaize County Regional  
Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

THOMAS W. STEINKE

LAND SURVEYING


2358 WAPAKONETA

Client MYRON ALTSTAETTER RR #1 WAPAKONETA  
County AUGLAIZE Twp. DUCHOUQUET Sec. 28 (S.E. 1/4)  
Drawn by JWS Scale 1" = 100' Drwg. No. 75-122  
Checked by D.R. Date JUNE 12 1975  
Sheet \_\_\_\_\_ of \_\_\_\_\_ (T 5 S 6 E)

358

# DESCRIPTION OF EASTERN 2.500 ACRES

Being 2.500 Acres in the South East quarter of Section 28, Town 5-S, Range 6-E, Duchouquet Township, Auglaize County, Ohio and being further described as follows:



Scale: \_\_\_\_\_

Commencing at a railroad spike at the North East corner of the South East quarter of Section 28, this point also being the PLACE OF BEGINNING. Thence with the east-west half section line of Section 28, South  $89^{\circ} 32' 30''$  West, 410.25 feet to an iron pin. Thence South  $0^{\circ} 07' 15''$  West, 265.27 feet to an iron pin. Thence North  $89^{\circ} 32' 30''$  East, 410.85 feet to a railroad spike in the center of Cemetary Road - T.R.# 161 and the east line of Section 28. Thence North  $0^{\circ} 00'$  East, 265.27 feet with said section line to a railroad spike and PLACE OF BEGINNING. Containing 2.500 Acres and being subject to all legal easements and rights-of-way of record.

# DESCRIPTION OF WESTERN 2.500 ACRES.

Being 2.500 Acres in the South East quarter of Section 28, Town 5-S, Range 6-E, Duchouquet Township, Auglaize County, Ohio and being further described as follows:

Commencing at a railroad spike at the North East corner of the South East quarter of Section 28. Thence with the east-west half section line of Section 28, South  $89^{\circ} 32' 30''$  West, 410.25 feet to an iron pin and PLACE OF BEGINNING. Thence continuing with said half section line, South  $89^{\circ} 32' 30''$  West, 410.25 feet to an iron pin. Thence South  $0^{\circ} 15' 30''$  West, 265.28 feet to an iron pin. Thence North  $89^{\circ} 32' 30''$  East, 410.85 feet to an iron pin. Thence North  $0^{\circ} 07' 15''$  East, 265.27 feet to an iron pin and PLACE OF BEGINNING. Containing 2.500 Acres and being subject to all legal easements and rights-of-way of record.

Survey and Description prepared by Thomas W. Steinke reg. surveyor #S-6177

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a (representative of the) County Commissioner(s) denotes approval of this plat.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Client \_\_\_\_\_ Twp. \_\_\_\_\_ Sec. \_\_\_\_\_  
County \_\_\_\_\_ Scale \_\_\_\_\_ Drwg. No. \_\_\_\_\_  
Drawn by \_\_\_\_\_ Date \_\_\_\_\_  
Checked by \_\_\_\_\_  
Sheet \_\_\_\_\_ of \_\_\_\_\_ (T S R E)

259

359