



Being 1.768 Acres in the N.W. cor. of N.E. $\frac{1}{4}$ of Section 27, Town 6-S, Range 5-East, Washington Township, Auglaize County, Ohio and more particularly described as follows:

Commencing at a railroad spike set in the N.W. cor. of N.E. qtr. of Section 27, said spike being in the centerline of S.R. 219 and Station 520+27.50 from the State right-of-way plans for S.R. 219 and also being the place of beginning.

Thence North 88°-39' East along the centerline of S.R. 219 a distance of 175.00 feet to a railroad spike.

Thence South 00°-59' East through an iron pin set in the South right-of-way line at 30.00 feet for a total distance of 440.00 feet to an iron pin.

Thence South 88°-39' West a distance of 175.00 feet to an iron pin set in the North-South half section line.

Thence North 00°-59' West along the North-South half section line a distance of 440.00 feet to a railroad spike and the place of beginning.

Containing 1.768 Acres and being subject to all legal easements and rights-of-way of record.

Survey and description prepared by Thomas W. Steinke Reg. Surveyor #S-6177

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s) denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

THOMAS W. STEINKE
LAND SURVEYING



Client MELVIN CLELAND RR#1 NEW KNOXVILLE
County AUGLAIZE Twp. WASHINGTON Sec. 27
Drawn by JOHN J. Scale 1" = 100' Drwg. No. 75-132
Checked by 2625 Date 7-4-75
Sheet 1 of 1

376

376

(T. 6 S; R. 5 E)