


LEGEND

- "A" = R.R. NAIL SET BY STATE
- "B" = RAILROAD SPIKE
- "C" = 5/8 INCH IRON BAR SET
- "D" = 1/2 INCH IRON BAR @ E. 1/4 POINT
- "E" = 3/4 INCH IRON 2.12 @ P.I. OF CURVE
- "F" = P.K. NAIL SET



LOCATION SKETCH
SECTION 32

CURVE DATA IN

$\Delta = 58^{\circ}22'45''$
 $D_c = 9^{\circ}00'$
 $L_s = 300'$
 $P = 5.98'$
 $Q_s = 13.5'$
 $K = 149.72'$
 $X_c = 298.34'$
 $Y_c = 23.47'$
 $R = 636.62'$
 $T = 508.67'$
 $L = 348.69'$
 $E = 99.35'$
 $\Delta_c = 31^{\circ}22'15''$

Scale: 1" = 200'


E. LAMPERT RD. RELOCATED

5.166 ACRES

11.892 ACRES

LIMITED ACCESS

SURVEYED BY Gordon L. Geeslin
 GORDON L. GEESLIN
 REGISTERED SURVEYOR 5372



REVISED 13 AUG. 1975

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s) denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

GORDON L. GEESLIN
 REGISTERED SURVEYOR
 ST. MARYS, OHIO

Client: LAMPERT ~ E. 1/4 OF E. 1/4 OF SEC. 32
 County: AUGLAIZE Twp. NOBLE Sec. 32
 Drawn by: G.G. Scale: 1" = 200' Drawn No. _____
 Checked by: " Date: 8-13-75
 Sheet: L of 2

August 12, 1975

Scale:

SURVEY DESCRIPTION

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the east half of the east half of Section 32, Township 5 South, Range 4 East, Being more particularly described as follows:

Beginning at a 1/2 inch iron bar at the east quarter point of said Section 32-

Thence, south 01°24'40" west along the east line of the southeast quarter of said Section 32 and the centerline of Lampert Road, a distance of ninety and 95/100 (90.95) feet to a railroad spike-

Thence, north 88°35'20" west, a distance of six hundred forty-five (645.00) feet to a point-

Thence, north 01°24'40" east, a distance of three hundred sixty-five (365.00) feet to a point-

Thence, north 60°05'21" east, a distance of four hundred three and 96/100 (403.96) feet to a point-

Thence, south 01°24'40" west, a distance of three hundred seventy-five (375.00) feet to a point-

Thence, south 88°35'20" east, a distance of three hundred (300.00) feet to a point on the east line of the northeast quarter of said Section 32 and the centerline of Lampert Road-

Thence, south 01°27'57" west, along the east line of the northeast quarter of said Section 32 and the centerline of Lampert Road, a distance of one hundred nine and 95/100 (109.95) feet to the place of beginning-


Containing 5.166 acres of land more or less.

Subject to all easements and right-of-way of record.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin
Registered Surveyor 5372



Signature by a representative of the County Engineer's Dept.
denotes approval of this plat meets taxmap plat requirements.
Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

GORDON L. GEESLIN
REG. SURVEYOR
385
OHIO

Client LAMPERT
County AUGLAIZE Twp. Noble Sec. 32
Drawn by GG Scale Not App. Draw. No. 1
Checked by GG Date 8-13-75
Sheet 2 of 2 385 (T 5 S; R 4 E)