

N




SURVEYED BY *Gordon L. Geeslin*
GORDON L. GEESLIN
REGISTERED SURVEYOR
5372

LEGEND.

- "A" = SPIKE FD. @ S.E. COR. NE 1/4 ~ NW 1/4 ~ SEC. 19 (SEE CO. RECORD)
- "B" = SPIKE FD. ON N-S 1/2 SEC. LINE SEC. 18 ON STATE PL.
- (SEE SHT. 52/116 OF STATE LAKE SURVEY)
- "C" = RAILROAD SPIKE SET.
- "D" = 1/2" IRON PIPE SET.
- "E" = 3/4" IRON PIPE SET.
- "F" = 5/8" IRON BAR SET.
- "G" = IRON BAR FD. ON CO. LINE (SEE CO. ENGRS. RECORDS.)

BEARINGS ARE MAGNETIC



SECTION 19

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

Signature by a representative of the County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

GORDON GEESLIN
REG. SURV. 5372
98 MARYS OHIO.

Client *DR. CURTISS H. LIBBEE*
County *AUGLAIZE* Twp. *ST. MARYS* Sec. *19*
Drawn by *GG* Scale *1"=200'* Draw No. _____
Checked by *GG* Date *NOV. 13, 1975*
Sheet *1* of *3*

PROPERTY DESCRIPTION - TRACT ONE

Being a parcel of land situated in St. Marys Township, Auglaize County, Ohio, in the northeast quarter of the northwest quarter of Section 19, Township 6 South, Range 4 East. Being more particularly described as follows:

Scale:

Beginning for reference at a railroad spike at the southeast corner of the northeast quarter of the northwest quarter of said Section 19-

Thence, north 01°51'10" west, along the east line of the northwest quarter of said Section 19, and the centerline of Schroeder Road, a distance of seven hundred forty-two and 15/100 (742.15) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing north 01°51'10" west, along the last described line, a distance of three hundred ten and 37/100 (310.37) feet to a railroad spike-

Thence, south 88°01'20" west, a distance of six hundred eighty-four and 72/100 (684.72) feet to a 5/8 inch iron bar-

Thence, south 02°00' east, a distance of forty-four and 88/100 (44.88) feet to a 5/8 inch iron bar-

Thence, south 84°37'58" west, a distance of two hundred forty-six and 74/100 (246.74) feet to a 3/4 inch iron pipe-

Thence, south 02°00' east, a distance of two hundred fifty and 90/100 (250.90) feet to a 1/2 inch iron pipe-

Thence, north 88°01'20" east, a distance of nine hundred thirty and 24/100 (930.24) feet to the place of beginning.

Containing 6.336 acres of land more or less.

Subject to all easements and right-of-way of record.

Surveyed by

Gordon L. Geeslin
Registered Surveyor 5372



Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.

Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.

Signed: _____ Date: _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.

Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.

Signed: _____ Date: _____

Gordon L. Geeslin
322 Concord Avenue
St. Marys, Ohio

Client: Dr. Arthur H. Libbee
County: Auglaize Twp. St. Marys, Sec. 19
Drawn by: J. D. Scale: _____
Checked by: E. J. Date: Nov. 19, 1974
Sheet: _____ of _____

(T. S. R. 10)

SURVEY DESCRIPTION - TRACT TWO

Being a parcel of land situated in St. Marys Township, Auglaize County, Ohio, in the northeast quarter of the northwest quarter of Section 19, Township 6 South, Range 4 East. Being more particularly described as follows:

Beginning at a railroad spike at the southeast corner of the northeast quarter of the northwest quarter of said Section 19-

Thence, north $01^{\circ}51'10''$ west, along the east line of the northwest quarter of said Section 19, and the centerline of Schroeder Road, a distance of seven hundred forty-two and $15/100$ (742.15) feet to a railroad spike-

Thence, south $88^{\circ}01'20''$ west, a distance of nine hundred thirty and $24/100$ (930.24) feet to a $1/2$ inch iron pipe-

Thence, south $02^{\circ}00'$ east, a distance of seven hundred forty-two and $15/100$ (742.15) feet to a railroad spike in the south line of the northeast quarter of the northwest quarter of said Section 19, and in the centerline of Koehn Road-

Thence, north $88^{\circ}01'20''$ east, along said south line of the northeast quarter of the northwest quarter of the centerline of Koehn Road, a distance of nine hundred twenty-eight and $38/100$ (928.38) feet to the place of beginning.

Containing 15.834 acres of land more or less.

Subject to all easements and right-of-way of record.

Surveyed by Gordon L. Geeslin

Gordon L. Geeslin
Registered Surveyor 5372



Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s) denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Gordon L. Geeslin
322 Concord Avenue
St. Marys, Ohio 45885

Client Dr. Curtiss H. Libbee
County Auglaize Twp. St. Marys Sec. 19
Drawn by _____ Scale _____ Draw. No. _____
Checked by G.L.G. Date Nov. 19, 1979
Sheet _____ of _____

100

100