


SURVEY RECORDED IN SURVEY BOOK B
PAGE 196

TOWN 6-S
RANGE 6-E
SECTION 4 NE $\frac{1}{4}$
PUSHETA TWP
AUGLAIZE Co.
OHIO




NORTH LINE SECTION 4
STATE ROUTE # 33
Scale: 1"=100'

SURVEY BY ROLLY E. PION

ERROR 6.38' N E S
1.01' E E W
6.46' TOTAL
E/C 1' : 172'

DEED BOOK 224
PAGE 539

DEED BOOK 218
PAGE 176



Thomas W. Steinke

N 1° 47' W
481.30

N 88° 23' 30" E
377.21

4.013 Ac.

356.17 TO E
S 88° 23' 30" W

354.00
S 0° 24' 30" E

CEMETERY ROAD T.R. #161

184° 15'
127.95
S 3° 50' 30" W
272.34
3° 50' 30" W
179° 04' 30"
S 2° 55' W 679.41
50° 08' 30" W
456.56
177° 13' 30"
177° 51' 30"

R.R. SPIKE SET
OVER P.K. NAIL
FOUND AT P.I.

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Thomas W. Steinke
LAND SURVEYING
WAPAKONETA & BOTKINS, OHIO

196

Client SANFORD McCauley
County AUGLAIZE Twp. PUSHETA Sec. 4
Drawn by W.S. Scale 1"=100' Drwg. No. 76-221
Checked by _____ Date APRIL 10, 1976
Sheet _____ of _____ (T 6 S 6 E)

196

DESCRIPTION OF 4.013 ACRES



Scale: _____

Being 4.013 Acres located in the North East quarter of Section 4,
Town 6 - S, Range 6 - E, Pusheta Township, Auglaize County, Ohio and being
further described as follows:

Commencing at the North East Corner of Section 4, said point being marked by
a railroad spike

Thence South $0^{\circ} 08' 30''$ West with the east line of Section 4 and the center
of Cemetery Road T. R. # 161, a distance of 456.56 feet to a railroad spike.

Thence South $2^{\circ} 55'$ West, a distance of 679.41 feet to a railroad spike.

Thence South $3^{\circ} 50' 30''$ West, a distance of 272.34 feet to a railroad
spike in the center of T.R. # 161 and the PLACE OF BEGINNING for the tract of land
herein described.

Thence continuing South $3^{\circ} 50' 30''$ West with said center, a distance of
127.95 feet to a railroad spike.


Thence South $0^{\circ} 24' 30''$ East, a distance of 354.00 feet to a railroad spike.

Thence South $88^{\circ} 23' 30''$ West, passing through an iron pin at 20.00 feet,
total distance of 356.17 feet to an iron pin.

Thence North $1^{\circ} 47'$ West, a distance of 481.30 feet to an iron pipe.

Thence North $88^{\circ} 23' 30''$ East, a distance of 377.21 feet to a railroad
spike in the center of Pusheta Road T.R. # 161 and the PLACE OF BEGINNING.

Containing in all 4.013 Acres and being subject to all legal easements and R/W of record
Survey recorded in Book B, Page 196 of the Auglaize County Records of Surveys.



Survey and description prepared by Thomas W. Steinke P.S. # 6177

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: _____ Date _____	Signature by a (representative of the) County Commissioner(s) denotes approval of this plat. Signed: _____ Date _____
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: _____ Date _____	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: _____ Date _____
THOMAS W. STEINKE LAND SURVEYING Wapakoneta & Botkins, Ohio 196 B	Client _____ County _____ Twp. _____ Sec. _____ Drawn by _____ Scale _____ Drwg. No. _____ Checked by _____ Date _____ Sheet _____ of _____ 196 B E