N.E. CORNER, S.E. QUARTER SECTION 9, CLAY TWA 5. 8735420"6 150.00 (20) R/W LINE Scale: 1"=60" N LOCATION PLAN 1.00 ACRES 80 LEGEND ---- R.R. SPK. SET O ..... IRON PIN SET DECTION ----- P.K. NAIL FOUND CLAY TWP. AUGLAIZE Co. Recorded in Survey PAGE 205 8" ENDPOST @ 1/4 SECTION CORNER 150.00 N. 87º 54/20"W. Being 1.00 Acre located in the South East quarter of Section Clay Township, Auglaize County, Ohio and being further allowed 9, Town 6 S, Range 7 F, described as follows: Commencing at a railroad spike at the North East corner of the South East quarter of Section 9, and the PLACE OF BEGINNING. Thence with a magnetic bearing of South 010,42! West with the east line of Section 9, a distance of 290.40 feet to an iron pin, passing through an iron pin at 20.0 feet Thence North 87° 54° 20" West, a distance of 150.00 feet to an iron pin. Thence North 01° 42° East, a distance of 290.40 feet to a railroad spike in the center of Clay Road T.R.# 126 and the half Section line of Section 9, passing through an iron pin at 270.40 feet. Thence South 87° 54' (40") East with the center of said road and half section line, a distance of 150.00 feet to a railroad spike and PLACE OF BEGINNING. Containing in all 1,00 Acres and being subject to all legal easements and R/W of record. Survey and Description prepared by Thomas W. Steinke # 6177 MARION OF OF komas W Z TATE OF Signature by a (representative of the County Commissioner(s) denotes approval of this plat. Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed:\_ Signature by a representative of the Auglaize County Regional Signature by a representative of the County Health Dept. Planning Commission denotes approval of this plat. denotes compliance with Health Regulations. Signed: Signed: \_ Thomas IF. Swinke JERRY LAMARR Client Twp. CLAY
Scale 1" \* 60 County AUGIAIZE LAND SURVEYING Drwg. No. 76-23 MHOL WAPAKONETA & BOTKINS, OHIO Drawn by Date 4-27-76 Checked by of (T 6 S; R 7 E) Sheet