



Dalton Lane owner

Total Dist 613.00'
500° 41' W


Dalton Lane owner

802.26
589° 58' W
Total Dist.

North & South
Half Section line

Total
11.565 AC.
0.477 AC R/W.

8.769
(w 1/2)



Bearing determined
from Vol. 156 p. 332
Aug. Co. Records

Scale:

1" = 100'

33.00'

179.01'

130.00'

105.30'

100° 49' 30" E

356.72'

33.00'

100° 49' 30" E

130.00'

105.30'

100° 49' 30" E

356.72'

33.00'

100° 49' 30" E

130.00'

105.30'

100° 49' 30" E

356.72'

33.00'

100° 49' 30" E

130.00'

105.30'

100° 49' 30" E

356.72'

33.00'

100° 49' 30" E

130.00'

105.30'

100° 49' 30" E

356.72'

33.00'

100° 49' 30" E

130.00'

105.30'

100° 49' 30" E

356.72'

33.00'

100° 49' 30" E

130.00'

105.30'

100° 49' 30" E

356.72'

33.00'

100° 49' 30" E

130.00'

105.30'

100° 49' 30" E

356.72'

33.00'

100° 49' 30" E

130.00'

105.30'

100° 49' 30" E

356.72'

I.P.

25.00'

Road R/W line

25.00'

I.P.

25.00'

I.P.

RRS.

623.25'
N 89° 58' E
CR# 150
formerly Middle Pike

209.11
N 89° 30' E

RRS.

I.P.: Iron Pipe
RRS.: Railroad Spike

Stone of the SE.
Cor. of the SW 1/4
of Sec. 29,
Union Twp.

Stone of the SW Cor.
of the SE 1/4 Sec. 29
Union Twp.

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Thomas E. Kuck

P.S. 4996

Client Dalton Lane to Jim Lackwood
County Auglaize Twp. Union Sec. 29
Drawn by J.W.E. Scale 1" = 100' Drwg. No. _____
Checked by _____ Date 16-76
Sheet 1 of 2

3- (T. 5 S. R. 5 E.)

222

222

NEW

THOMAS E. KUCK
ENGINEERING AND SURVEYS
REGISTERED ENGINEER NO. 28943
REGISTERED SURVEYOR NO. 4996
1820 BIBLE ROAD - LIMA, OHIO
PHONE 225-6871

CLIENT Lane to Lockwood
COUNTY Auglaize TOWNSHIP UNION
SECTION 29 LOT NO. _____
DATE 2-16-76 COMPUTED BY _____ SURVEYED BY _____
SHEET NO. 2 OF 2

LANE TO LOCKWOOD
SURVEYORS DESCRIPTION

The following described tract of land is part of the Southwest Quarter and part of the Southeast Quarter of Section 29. Town 5 South, Range 7 East, Union Township, Auglaize County, Ohio, and is more particularly described as follows.
The PLACE OF BEGINNING being the stone at the center of Section 29, Union Township, and the South line of Section 29 Union Township. (Stone being in the center of County Road #150, formerly Middle Pike.

Thence N 89° 30'E, along the center of County Road #150, formerly Middle Pike, 209.11 feet to a railroad spike on the Westerly right of way line of the D.T.&I. Railroad.

Thence N 00° 49' 30"E, along the Westerly right of way line of the D.T.&I. Railroad 356.72 feet to an iron pipe.

Thence N 17° 26' 30"W, along the Westerly right of way line of the D.T.&I. railroad 105.30 feet to an iron pipe.

Thence N 00° 49' 30"E along the Westerly right of way line of the D.T.&I. railroad 150.00 feet to an iron pipe.

Thence N 19° 05' 30"E along the Westerly right of way line of the D.T.&I. railroad 4.39 feet to an iron pin.

Thence S 89° 58'W (passing through an iron pipe set at 179.01 feet on the North and South half section line of Section 29) 602.26 feet to an iron pipe.

Thence S 00° 41'W (passing through an iron pipe set at 588.00 feet) 613.00 feet to a railroad spike in the center of County Road #150, formerly Middle Pike.

Thence N 89° 58'E along the center of County Road #150, formerly Middle Pike, 623.25 feet to the stone at the center of Section 29 Union Township and on the South line of Section 29 Union Township, which was the PLACE OF BEGINNING.

The above described tract of land contains 11.565 acres more or less subject to 0.477 acres dedicated to the public for highway purposes and to all legal easements of record.

