

from CARL CRAFT

Situate in the southwest quarter of Section 14, Noble Township, Town 5 South, Range 4 East, with respect to the First Principal Meridian, Auglaize County, Ohio and more particularly described as follows:

Commencing at the southeast corner of the southwest quarter of Section 14; thence NOOO45'00"E a distance of 601.26 feet along TR 55 to an iron pin; thence N59°32'20"W a distance of 446.26 feet to an iron pin; thence N30°22'55"E a distance of 388.90 feet to the PLACE OF BEGINNING; thence continuing N30°22'55"E a distance of 20.00 feet; thence S44^O37'05"E a distance of 36.23 feet; thence S30°22'55"W a distance of 20.00 feet; thence N44^o37'05"W a distance of 36.23 feet to the PLACE OF BEGINNING.

The above tract of land contains 0.016 acres. Surveyed by the Auglaize County Engineering Department, 1014 S. Blackhoof Street, Wapakoneta, Ohio.

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date	Signature by a (representative of the) County Commissioner(s) denotes approval of this plat. Signed: Date
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: Date
Auglaize County Client Cu	Vert No. NOB - 55- 4.22 Sec. 14 Sec. 14

234 akoneta, Ohio

Client Culvert No.	NOB - 55- 14.22
County Auglaize	Twp. MODIC Sec. 13
Drawn by D. G. B	The state of the s
Checked by	Date 1976-04-29
Sheet of Z	T 5 R P K