


Being 1.99 Acre located in the South East quarter of Section 30, Logan Township T-4-S, R-5-E, Auglaize County, Ohio, being further described as follows:

Commencing at a monument box in the South East corner of Section 30, Logan Township, Auglaize County, Ohio;
 Thence S. 88° 45' 40" W. with the center line of C.R.#210 a distance of 1327.07 feet to a R.R. Spike and the PLACE OF BEGINNING;
 Thence continuing S. 88° 45' 40" W. a distance of 269.0 feet to a R.R. Spike;
 Thence N. 01° 42' 20" W. a distance of 322.60 feet to an Iron Pin, passing through an Iron Pin set in the Right-of-Way of C.R.#210 at a distance of 25 feet;
 Thence N. 88° 45' 40" E. a distance of 269.0 feet to an Iron Pin;
 Thence S. 01° 42' 20" E. a distance of 322.60 feet to a R.R. Spike which was the PLACE OF BEGINNING, passing through an Iron Pin set in the Right-of-Way of C.R.#210 a distance of 297.60 feet.

The above tract of land contains 1.99 Acres and is subject to a 25.0 foot half Right-of-Way on C.R.# 210.

Survey and Description prepared by Thomas W. Steinke. Survey recorded in book B, page 241, of the Auglaize County Survey Records.



Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
 Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s) denotes approval of this plat.
 Signed: _____ Date _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
 Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
 Signed: _____ Date _____

Thomas W. Steinke
 LAND SURVEYING
 WAPARONETA & DOTKINS, OHIO



Client JACK CORE
 County AUGLAIZE Twp. LOGAN Sec. 30
 Drawn by JOHN J. Scale 1"=100' Drwg. No. 76-234
 Checked by TOM Date MAY 13, 1976
 Sheet 1 of 1 (T 4 S; R 5 E)