



TOWN 6-S
RANGE 6-E
SEC 22 S.W ¼
PUSHETA TWP.
AUGLAIZE CO.
OHIO

LEGEND

O=IRON PIN SET
●=RR SPIKE SET
X=RR SPIKE FD.



1/2 SEC. LINE

Scale:
1" = 200'

STONE DUG FOR
E.F.D. PLACED
1 1/4" IRON PIN

TR# 163

ROAD

STONE FO

N 86° 55' W
402.70

6.68 Ac.

5 3° 35' W
713.84

713.82

N 2° 47' 40" E

SECTION LINE

S.W. COR.
SEC. 22

1998.25

412.58

S 86° 55' E

C & New Knoxville - Santa Fe Road CR#100
60' R/W

No STONE
SEC. LINE

STONE DUG FOR
NOT FOUND
PLACED R.R. SPIKE

There are two old surveys monumenting Section 22, one dated 1850 and the other 1903. The earlier survey was reestablished and an error of approximately 15 ft. was found in the survey on the south line of Sec. 22. Survey of 1903 was reconstructed as near as possible and stones found from this survey are noted. The later of the two surveys was held as close as the survey was performed in 1903. A combination of existing monuments, fence lines, previous surveys and arial photos was used to establish the property lines shown hereon. The stones in New Knoxville-Santa Fe Road may have been lost in the reconstruction of the road in 1956.

Survey performed by Thomas W. Steinke reg. surveyor # 6177

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Client JEROME SCHAUB

County AUGLAIZE Twp. PUSHETA Sec. 22

Drawn by JWS Scale 1" = 200' Drwg. No. 76-238

Checked by _____ Date MAY 1976

Sheet 1 of 2

(T 6 ~~SECRET~~)

242

242

DESCRIPTION OF 6.68 ACRES



Scale: _____

Being part of the South West quarter of Section 22, Town 6 -S, Range 6 -E, Pusheta Township, Auglaize County, Ohio and being further described as follows:

Commencing at a railroad spike located at the South West corner of Section 22, said point being the intersection of (Cemetery Road) T.R.# 161 and (New Knoxville - Santa Fe Road) C.R.# 100.

Thence with a magnetic bearing of South $86^{\circ} 55'$ East with the south line of Section 22 and the center of C.R.# 100, a distance of 1998.25 feet to a railroad spike and PLACE OF BEGINNING for the tract of land herein described.

Thence South $86^{\circ} 55'$ East, a distance of 412.58 feet along the center of C.R.# 100 to a railroad spike.

Thence North $02^{\circ} 47' 40''$ East, a distance of 713.82 feet to an iron pin.

Thence North $86^{\circ} 55'$ West, a distance of 402.70 feet to an iron pin.

Thence South $03^{\circ} 35'$ West, a distance of 713.84 feet to a railroad spike in the south line of Section 22, center of C.R.# 100 and the PLACE OF BEGINNING.

Containing in all 6.68 Acres and being subject to all legal easements and R/W of record.

Survey recorded in Survey Book -B Page 242 of the Auglaize County Survey Records.

Survey and Description prepared by Thomas W. Steinke

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s) denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

242

Client _____
County _____ Twp. _____ Sec. _____
Drawn by _____ Scale _____ Drwg. No. _____
Checked by _____ Date _____
Sheet _____ of _____ (T _____ S _____ R _____ E) _____

242a