


"B" 280

SECTION LINE  
COUNTY LINE

N.W. CORNER  
SECTION 6



SECTION 6NW1/4, T-5-S, R-7-E  
UNION TWP, AUGLAIZE CO., OHIO



Scale:  
1"=100'

SECTION LINE  
1163.9'

SELLARS ROAD 50' R/W

TOWN-LINE LIMA ROAD 60' R/W  
N. 2° 50' E.

594.0'

(30)

536.45'

(30)

S 87° 10' E  
406.0'

5.000 Δc.

536.45'  
S. 2° 50' W.

406.0'  
N. 87° 10' W

LEGEND

- ..... R.R. SPIKE SET
- ..... IRON PIN SET
- ..... STONE
- ✱..... R.R. SPIKE FOUND



Signature by a representative of the County Engineer's Dept.  
denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a (representative of the) County Commissioner(s)  
denotes approval of this plat.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the County Health Dept.  
denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the Auglaize County Regional  
Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Thomas W. Steinke  
LAND SURVEYING  
17 MONETA & BOTKINS, OHIO



Client RAYMOND ROBERTS  
County AUGLAIZE Twp. UNION Sec. 6  
Drawn by JOHN J. Scale 1"=100' Drwg. No. 76-244  
Checked by \_\_\_\_\_ Date JUNE 23<sup>RD</sup>, 1977  
Sheet 1 of 2  
(T-5 S; R-7)

280

280



# THOMAS W. STEINKE LAND SURVEYING

PH: 693-4853

ROUTE #1,  
BOTKINS, OHIO

## Description of 5.000 Acres

Being 5.000 Acres located in the North West quarter of Section 6, Town 5-S, Range 7-E, Union Township, Auglaize County, Ohio and being further described as follows:

Commencing at a corner stone located at the North West corner of Section 6.

Thence South  $02^{\circ} 50'$  West, with the center of C.R.# 191 ( Town-Line Lima Road) and the west line of Section 6, a distance of 1163.9 feet to a railroad spike at the intersection of T.R.# 198 (Sellers Road)

Thence continuing South  $02^{\circ} 50'$  West, a distance of 594.00 feet to a railroad spike and PLACE OF BEGINNING.

Thence South  $87^{\circ} 10'$  East, a distance of 406.00 feet to an iron pin.

Thence South  $02^{\circ} 50'$  West, a distance of 536.45 feet to an iron pin.

Thence North  $87^{\circ} 10'$  West, a distance of 406.00 feet to a railroad spike in the center of C.R.# 191 and the west line of Section 6.

Thence North  $02^{\circ} 50'$  East with said center line and section line, a distance of 536.45 feet to a railroad spike and PLACE OF BEGINNING. Containing in all 5.000 Acres and being subject to all legal easements and R/W of record

Survey Recorded in Survey Book B Page 281 of the Auglaize County Survey Records.

This is a corrective survey to superceed Deed Book 231, Page 274 Survey and Description prepared by Thomas W. Steinke # 6177