The latest section of	4 (J Games Cand Some		
	N.W. CORNER	SECTION		
***************************************	SECTION G			Y
20				Scale:
50				1"=100
3 2		SECTION GN UNION TWA	W4, T-5-3, R-7-E Auguare Ca, On.	
1		,	Co, Ci,	
(0.00 + 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1		SELLARS ROAD 5.88°34'20"	50' %	-
	(25)	317.81	E. (25')	
	- Constanting			The state of the s
	Confidence of the confidence o			
\3			Name of the Control o	
7/2,09	R-Charles and Control of the Control		- down	
30	Children Copy and Cop		TO POSSIBLE STATE OF THE POSSIBLE STATE OF T	LEGEND
0	Discriptions		0.	RRSPIKE SET
ROAD	egrina-rotaeres	5001 A	<u> </u>	STONE
	PRODUCE I DODGE	<u> 5.001 </u>	IC.	
Ψ.	ω,]	
_	30.		30"	
N N	°56′			
1	9		685. 2°56	
- NWO	ヹ		3	
ř				
	Billion of the Control of the Contro		Towns and the second se	
of Melonic Phase and an analysis of Melonic Phase and American Ame				DO OF OF
si Januari (s. spec) (shandhal			The state of the s	* THOMAS W
	95 (17) (18) (18) (18) (18) (18) (18) (18) (18		appaga	STEINKE
	- Company	317.81	The state of the s	S 6177 O STERE
		N. 88°34'20"W).	ANE AO ANE AO

ture by a reples that this p	presentative of the County Er lat meets tax map plat require Da	ements. denot	ture by a (representative of the es approval of this plat.	
	Da	Signed	d:	Date
ture by a r	epresentative of the County	Health Dept. Signat	ure by a representative of the	Auglaize County Regional
les complianc	e with Health Regulations.	Planni	ng Commission denotes approv	al of this plat
Thomas M.		Client RAYMO County Auguster Drawn by	Twp. Union	Sec. 6
LAND SURY	CETING OTKINS.OHIO	Drawn by John Checked by	J. Scale 1″=100′ Date 6	_Drwg. No.76-244 -25-76

THOMAS W. STEINKE LAND SURVEYING



PH: 693-4853

ROUTE #1, BOTKINS, OHIO

Description of 5.001 Acres

Being 5.001 Aures located in the North West quarter of Section 6, Town 5-S, Range 7-E, Union Township, Auglaize County, Ohio and Commonsisted as follows:

Commencing at a corner stone located at the North West corner of

Thence South 02° 50° West, with the center of C.R.# 191 (Town-Line Lima Road) and the west line of Section 6, a distance of 1163.9 feet to a railroad spike at the intersection of T.R.# 198 (Sellars

Thence South 88° 34° 20" East, with the center of T.R.# 198 and the quarter section line of said Section, a distance of 688.05 feet to a railroad spike and PLACE OF BEGINNING.

Thence South 88° 34. 20° East with said center line, a distance of 317.81 feet to a railroad spike.

Thence South 02° 56' 30" West, a distance of 685.46 feet to an iron pin, passing through an iron pin at 25.0 feet.

Thence North 88° 34° 20" West, a distance of 317.81 feet to an iron pin. Thence North 02° 56° 30" East, a distance of 685,46 feet to a rail-road spike in the center of T.R.# 198, passing through an iron pin at 660.46 feet, and the PLACE OF BEGINNING.

Containing in all 5.001 Acres and being subject to all legal easements and R/W of record.

Survey Recorded in Survey Book B Page 283 of the Auglaize County Survey Records.

Survey and Description prepared by Thomas W. Steinke # 6177