



Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Thomas W. Steinke
LAND SURVEYING
TAPAKONETA & BOTKINS, OHIO



Client RAYMOND ROBERTS
County AUGLAIZE Twp. UNION Sec. 6
Drawn by HANSE Scale 1"=100' Drwg. No. 76-244
Checked by _____ Date 6-25-76
Sheet 1 of 2

292

(T. 5 S. R. 7 E. S. 6) 292

THOMAS W. STEINKE

LAND SURVEYING



PH: 693-4853

ROUTE #1,
BOTKINS, OHIO

Description of 5.001 Acres

Being 5.001 Acres located in the North West quarter of Section 6, Town 5-S, Range 7-E, Union Township, Auglaize County, Ohio and being further described as follows:

Commencing at a corner stone located at the North West corner of Section 6.

Thence South $02^{\circ} 50'$ West, with the center of C.R.# 191 (Town-Line Lima Road) and the west line of Section 6, a distance of 1163.9 feet to a railroad spike at the intersection of T.R.# 198 (Sellers Road).

Thence South $88^{\circ} 34' 20''$ East, with the center of T.R.# 198 and the quarter section line of said Section, a distance of 364.25 feet to a railroad spike and PLACE OF BEGINNING.

Thence South $88^{\circ} 34' 20''$ East with said center line, a distance of 323.80 feet to a railroad spike.

Thence South $02^{\circ} 56' 30''$ West, a distance of 685.46 feet to an iron pin, passing through an iron pin at 25.0 feet.

Thence North $88^{\circ} 34' 20''$ West, a distance of 280.49 feet to an iron pin.

Thence North $02^{\circ} 50'$ East, a distance of 81.47 feet to an iron pin.

Thence North $87^{\circ} 10'$ West, a distance of 41.85 feet to an iron pin.

Thence North $02^{\circ} 50'$ East, a distance of 602.92 feet to a railroad spike in the center of T.R.# 198, passing through an iron pin at 577.92 feet, and the PLACE OF BEGINNING.

Containing in all 5.001 Acres and being subject to all legal easements and R/W of record.

Survey Recorded in Survey Book B Page 293 of the Auglaize County Survey Records.

Survey and Description prepared by Thomas W. Steinke # 6177