<u>-</u>		ION LINE		
N.W. CORNER	Cour	ITY LINE		-12
SECTION 6				Ÿ
<u> </u>				Soula
	-			Scale: 1"=100"
200				
63.9				
181=	SECTION	N GNWK, T-	0-0,92-7-E 12e Co., Ou	
		,		
7				
	LARS R	POAD 5	01/2	
	<u>5.88°3.</u> 317.8	<ul> <li>— выполнением на мозифойбимостим им</li> </ul>	(25)	number respectations are required by the section of
(25)	517.0	) l	(25')	
and the second s				•
3		677		
2				
				•
60'R/				LEGEND
				OR.R.SPIKE SET
DAON .				0
8		/ /		9,000
02	D_ <i>UU</i> ,	$/\Delta C.$		
Σ			3	
, (e			30	
m > 1			300	
2°56'2				
2,10			685	
7   0 9			10	
L S L			N	
10				
			· Landing Company	
				TE OF
				ALES TO THE REAL PROPERTY OF T
				* THOMAS W. *
				STEINKE
				S-6177 0/ 8
1				STERE ALL
<u></u>	317.0 N.88°34	DI		PANTONIETO
2, 201	N.00- 32	LO W.		- committee
B' 294				
Signature by a representative of the County Engin lenotes that this plat meets tax map plat requireme	neer's Dept.			ive of the) County Commissioner(s)
enotes that this plat meets tax map plat requireme ligned: Date	1193,	Signed:	or one pla	Date
Signature by a representative of the County H denotes compliance with Health Regulations.	ealth Dept.	Planning Co	mmission denot	ve of the Auglaize County Regional les approval of this plat.
denotes compliance with Health Regulations.  Signed: Date		Signed:		Date
				the state of the s
	Client R.	AYMOND	ROBERT	T.5
Thomas W. Steinter	County A	MLAIZE	Twp. UN Scale 1"	NON Sec. 6
LAND SURVEYING	Checked by	JOHN J.		Date 6-25-76
WARAKONETA & BOTKINS.OHIO	SheetI	of a		(T 5 S 7 7 C)

\_3

## THOMAS W. STEINKE LAND SURVEYING



PH: 693-4853

ROUTE #1, BOTKINS, OHIO

## Description of 5.001 Acres

Being 5.001 Aures located in the North West quarter of Section 6, Town 5-S, Range 7-E, Union Township, Auglaize County, Ohio and being further described as follows:

Commencing at a corner stone located at the North West corner of Section 6.

Thence South 02° 50° West, with the center of C.R.# 191 ( Town-Line Lima Road) and the west line of Section 6, a distance of 1163.9 feet to a railroad spike at the intersection of T.R.# 198 (Sellars Road).

Thence South 88° 34° 20" East, with the center of T.R.# 198 and the quarter section line of said Section, a distance of 1005.86 feet to a railroad spike and PLACE OF BEGINNING.

Thence South 88° 34° 20" East with said center line, a distance of 317.81 feet to a railroad spike.

Thence South 02° 56° 30" West, a distance of 685.46 feet to an iron pin, passing through an iron pin at 25.0 feet.

Thence North 88° 34° 20" West, a distance of 317.81 feet to an iron pin. Thence North 02° 56° 30" East, a distance of 685,46 feet to a rail-road spike in the center of T.R.# 198, passing through an iron pin at 660.46 feet, and the PLACE OF BEGINNING.

Containing in all 5.001 Acres and being subject to all legal easements and R/W of record.

Survey Recorded in Survey Book B Page 295 of the Auglaize County Survey Records.

Survey and Description prepared by Thomas W. Steinke # 6177