Scale: FENCE LINE 7 856.0 × 589016'Ex x 580.LINE
D.B. 189 PG. 976 D.B. 209 PG. 426 PG. 426 PG. 976 P
366.28 N. 301.71 S. 301.71
N 89°50' 40" W 0.8. 139 Pt. 78
The above parcel was surveyed useing existing deeds, State of Ohio R/W plans, Survey records and existing features. There is a error in the deeds showing both excesses and shortages surrounding the above surveyed area. Thomas W Stake
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date Signed: Signed: Date Signed: Date Signed: Date Signed: Date Date
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: Date
Client STEVE WINSLOW County AUGLAIZE Twp. DUCHOLOGIESec. 2 Drawn by 1620 Scale 1" = 200' Drwg. No. 76-289 Checked by 165 Date AUGUST DISC. Sheet 1 of 3 (T. 46.66 F)

THOMAS W. STEINKE LAND SURVEYING

PM: 693-4853

ROUTE #1, BOTKINS, OHIO

(T_4, S; R 6 E)

Being 10.80 Acres located in the North-East quarter of Section 2, T-L-S, R-6-E, Duchouquet Township, Auglaize County, Ohio and being further described as follows:

Commencing at a stone located at the N.W. cor. of the N.E. qtr. of Sec. 2. Thence eastward with the north line of Section 2, a distance of 856.0 feet to an iron pin and PLACE OF BEGINNING. Thence continueing with said section line South 89° 16° East, a distance of 435.60 feet to an iron pin in the western R/W line of Interstate # 75 at Station 659+76.5 and 125.0 feet left of center line. Thence southward with the westernR/W line of I-75 on a radius of 5604.58 feet to an iron pin located at Station 651+30.5 and 125.0 feet left of the center line of I-75. Thence North 89° 50° 40° West, a distance of 902.83 feet to a P.K. nail set in the center line of C.R.# 25-A prior to 1942. Thence North 28° 11° East with said center line, a distance of 308.63

Thence North 28° 11° East with said center line, a distance of 308.63 feet to an iron pin. Thence South 89° 11° East, a distance of 301.71 feet to an iron pin. Thence North 01° 01° East, a distance of 168.52 feet to an iron pin. Thence South 89° 16° East, a distance of 151.28 feet to an iron pin. Thence North 01° 01° East, a distance of 380.55 feet to an iron pin and PLACE OF BEGINNING.

Containing in all 10.80 Acres and being subject to all legal easements and R/W of record.

Survey recorded in survey book "B" Page 327.

ALSO: Atract of land containing 3.87 As.surveyed by the State of Ohio for right-of-way purposes in the construction of Interstate # 75 and described in Deed Book 162, Page 72 of the Auglaize County Deed Records.

AAS W. STERVE Land Surveying 106 Park Street oakoneta, Ohio 45695

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: for political S. D. of: Date		Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: Date
		Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date
TOTAL W. STEMME Land Surveying 103 Park Street	County Au Drawn by	EVE WINSLOW GLAIZE TWP. DUCHOUQUETEC. 2 2002 Scale 1" = 200' Dry NOVO 89 Date AUGUS 6975

Sheet__1_of_3