

LEGEND

- "A" = STONE @ N.W. COR. SEC. 29 (SEE STATE REF.)
- "B" = FD. IRON BAR @ W. 1/4 PT. OF SEC. 29. DUG FOR STONE W/ NO SUCCESS BUT, FOUND OLD WOOD STAKE & IRON BAR 2' DEEP.
- "C" = FD. 5/8 INCH IRON BAR FROM "STIMMEL" SURVEY @ S.E. COR. W. 1/2 - NW. 1/4 - SEC. 29.
- "D" = HARROW TOOTH SPIKE SET.

- ALL OTHER POINTS SHOWN THUS "•" ARE 5/8" IRON BARS. -

THE W. LINE OF THE N.W. 1/4 WAS ASSUMED TO BEAR S. 00° 30' W.

SURVEYED BY Gordon L. Geeslin
GORDON L. GEESLIN
REGISTERED SURVEYOR N° 5372



LIECHTY SURVEY - PART OF THE WEST HALF OF THE NORTHWEST QUARTER OF SECTION 29, TOWN 6 SOUTH, RANGE 4 EAST (ST. MARYS TOWNSHIP), AUGLAIZE COUNTY, OHIO.

OCTOBER, 1976

SCALE 1" = 100'

Redrawn and Filed B-349
10/21/76 DMC

349

COMM. NO.	DRAWN BY	GORDON L. GEESLIN	DATE	REVISION DATE	SHEET NO.
	CHECKED BY	REGISTERED SURVEYOR CELINA, OHIO 45822			1 of 2

October 18, 1976



SURVEY DESCRIPTION

Scale: _____

Being a parcel of land situated in St. Marys Township, Auglaize County, Ohio, in the west half of the northwest quarter of Section 29, Township 6 South, Range 4 East. Being more particularly described as follows:

Beginning at an iron bar at the west quarter post of said Section 29-

Thence, south $89^{\circ}32'20''$ east, along the east-west half section line of said Section 29, a distance of nine hundred forty and $04/100$ (940.04) feet to a point-

Thence, north $18^{\circ}57'04''$ west, a distance of one hundred twenty-three and $47/100$ (123.47) feet to a $5/8$ inch iron bar. Said line passing through a $5/8$ inch iron bar at eight and $79/100$ (8.79) feet-

Thence, north $54^{\circ}02'24''$ west, a distance of one hundred sixteen and $17/100$ (116.17) feet to a $5/8$ inch iron bar-

Thence, north $67^{\circ}13'06''$ west, a distance of eighty-six and $54/100$ (86.54) feet to a $5/8$ inch iron bar-

Thence, north $03^{\circ}15'44''$ west, a distance of ninety-four and $91/100$ (94.91) feet to a $5/8$ inch iron bar-

Thence, north $62^{\circ}11'19''$ west, a distance of one hundred forty and $18/100$ (140.18) feet to a $5/8$ inch iron bar-

Thence, north $07^{\circ}46'06''$ east, a distance of one hundred twenty-three and $13/100$ (123.13) feet to a $5/8$ inch iron bar-

Thence, north $22^{\circ}36'40''$ west, a distance of seventy-eight and $78/100$ (78.78) feet to a $5/8$ inch iron bar-

Thence, south $72^{\circ}56'21''$ west, a distance of six hundred six and $48/100$ (606.48) feet to a harrow tooth spike on the west line of the northwest quarter of said Section 29 and the centerline of State Route 364-

Thence, south $00^{\circ}30'$ west, along said west line of the northwest quarter of Section 29, and the centerline of State Route 364, a distance of three hundred eighty-seven and $86/100$ (387.86) feet to the place of beginning.

Containing 8.353 acres of land more or less.


Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated October, 1976, on file in the County Engineer's Office.

Surveyed By

Gordon L. Geeslin
Gordon L. Geeslin

Registered Surveyor #5372



Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

Signature by a (representative of the) County Commissioner(s) denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

GORDON L. GEESLIN
REGISTERED SURVEYOR
CELINA, OHIO. 350

Client LIECHTY
County AUGLAIZE Twp. ST. MARYS Sec. 29
Drawn by GG Scale _____ Drwg. No. _____
Checked by _____ Date 5-18-76
Sheet 2 of 2 (T 6 S 1 R 4 E)

350