



Being part of the S.W. $\frac{1}{4}$ of Section 29, T-6-S, R-5-E, Washington Township, Auglaize County, Ohio and being further described as follows:

Commencing at an iron pin found at the S.W. corner of lot # 2 in Hoge Subd. New Knoxville, said point being on the south Corporation line.

Thence east with the south corp. line of New Knoxville, 154.0 feet to an iron pin set;

Thence south with an interior angle of $89^{\circ} 17'$, 16.5 feet to an iron pin set;

Thence west with an interior angle of $90^{\circ} 43'$, 154.0 feet to an iron pin set;

20.0 feet east of the west line of Section 29.

Thence north with an interior angle of $89^{\circ} 17'$, 16.5 feet to an iron pin and

PLACE OF BEGINNING.

Being subject to all legal easements and R/W of record.

Survey recorded in Survey Book C Page 1 of the Auglaize Co. Survey Record

Survey and desc. prepared by Thomas W. Steinke Reg. Surveyor # 6177

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: _____ Date _____	Signature by a (representative of the) County Commissioner(s) denotes approval of this plat. Signed: _____ Date _____
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: _____ Date _____	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: _____ Date _____

Surveyor LAND SURVEYING Wapakoneta & Botkins, Ohio	Client DON HENKENER County AUGLAIZE Twp WASHINGTON Sec 29 SW 1/4 Drawn by THS Scale 1" = 50' Drwg No. 76-210 Checked by _____ Date 12-4-16 Sheet _____ of _____ (T-6-S-R-5-E)
--	---