

Being 7.00 Acres located in the north-west quarter of Section 9, T-6-S, R-8-E, Goshen Township, Auglaize County, Ohio and being further described as follows:

Commencing at a P.K. nail and shiner found at the North-East corner of the North-West quarter of Section 9 and the PLACE OF BEGINNING.

Thence South 04° 20' West with the half section line of Section 9, a distance of 835.40 feet to an iron pin set.


Thence North 85° 55' West, 365.00 feet to an iron pin set.

Thence North 04° 20' East, 835.40 feet to a railroad spike set in the center of T.R.# 130 and the north line of Section 9, passing through an iron pin at 815.40 feet.

Thence South 85° 55' East with said center line and section line, a distance of 365.00 feet to the PLACE OF BEGINNING.

Containing in all 7.00 Acres and being subject to all legal easements and R/W of record.

Survey and description prepared by Thomas W. Steinke Registered Surveyor # 6177 and recorded in Survey Book C Page 21 of the Auglaize County Survey Records.



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.

Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.

Signed: _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat.

Signed: _____ Date _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.

Signed: _____ Date _____

Thomas W. Steinke
LAND SURVEYING
WYAKONETA & HOTKINS, OHIO

Client WM. HODDE
County AUGLAIZE Twp. GOSHEN Sec. NINE
Drawn by G.E.M. Scale 1" = 200 Drwg. No. 77-333
Checked by _____ Date _____
Sheet 1 of 1 (T 6 S; R 8 E)