



Being 11.762 Acres located in the north-east quarter of Section 7, T-6-S, R-6-E, Pusheta Township, Auglaize County, Ohio and being further Described as follows.

Commencing at a railroad spike located at the south-east corner of the north-east quarter of Section 7, also being the center line intersection of CR 133A (Hardin-Wapak Rd) and TR #126 (Owl Creek Rd.). Thence on a magnetic bearing of N 87° 59' W with the 1/2 section line and the center of TR#126, 664.20 feet to a railroad spike and PLACE OF BEGINNING. Thence continuing N 87° 59' W, a distance of 666.92 feet to a railroad spike. Thence N 02° 15' E with the north-south 1/4 section line, a distance of 768.85 feet to an iron bar set. Thence S 88° 06' 15" E, a distance of 664.73 feet to a nail set in a wood corner post. Thence S 02° 05' W, a distance of 770.25 feet to a railroad spike and PLACE OF BEGINNING, passing through an iron bar at 745.25 feet. Containing in all 11.762 Acres and being subject to all legal easements and R/W of record. Survey prepared by Thomas W. Steinke. Survey Book C Page 24

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date: _____
for political S. D. of: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

Thomas W. Steinke
LAND SURVEYING
PUSHETA & HOTKINS, OHIO

Client HAROLD HARROD
County AUGLAIZE Twp. PUSHETA Sec. 7 NE 1/4
Drawn by WDS Scale 1" = 200 Drwg. No. 77-335
Checked by _____ Date FEB 15, 1977
Sheet _____ of _____
(T-6-S-R-6-E)