


PUSHETA ROAD -
TR#120

TOTAL = 99.188 Δc. (20.181 Δc. EAST ½ SEC. 18) (79.007 Δc. WEST ½ SEC. 18)
NORTH HALF = 49.594 Δc. (10.102 Δc. EAST ½ SEC. 18) (39.492 Δc. WEST ½ SEC. 18)
SOUTH HALF = 49.594 Δc. (10.079 Δc. EAST ½ SEC. 18) (39.515 Δc. WEST ½ SEC. 18)



6-S
TOWN

7-E
RANGE

CLAY
TOWNSHIP

18 NE ¼ NW ¼
SECTION

AUGLAIZE
COUNTY

OHIO
STATE

1"=200'
SCALE

3-25-77
DATE

74-329
FILE NO.

RECORDED IN SURVEY BOOK "C" PAGE 36

SET CORNER BY SPLITTING THE
WEST LINE OF N.W. ¼

ORIGINAL CORNER
STONE FOUND BY
WOOD CORNER POST

2646.3 BY ORIGINAL SURVEY
2646.5 ACTUAL

SECTION LINE
TOWNLINE-LIMA RD. CR# 191

SECTION LINE

1323.25

661.93

R.R. SPIKE SET

N 89° 45' 10" E

2601.60

N 89° 50' 30" E 657.22

6" DIA STEEL POST

49.594 Δc.

R.R. SPK. SET

S 89° 45' 10" W
N 89° 45' 10" E

3269.16
3269.16

N 00° 02' 20" E
661.32

S.W. COR.
N.W. QTR.
SEC. 18

P.K. FD.

S 89° 41' 30" W

2605.15

S 89° 49' W 674.35

SECTION CORNER
BY AUGLAIZE CO.
REFERENCES

P.K. FD.

I.P. FD.

I.P. FD.

½ SEC. LINE

I.P. SET.

I.P. SET.

CENTER OF SEC. 18

CORNER STONE NOT
RECOVERED. CORNER
SET USING PREVIOUS
SURVEYS OF RECORD

EXISTING FENCE
LINE USED, CONSENT
BY COMMON PARTIES
AS THE PROPERTY
LINE OF INTENT

SECTION LINE
ASHBURN RD. CR# 201

REFERENCES		
DEED	BOOK	PAGE
	235	671
	172	260
	145	555
	154	255
	232	303
C.T.	4	349
	139	237
	230	610
	196	343

AUGLAIZE RECORD OF SURVEYS
RIGHT-OF-WAY RECORDS
ORIGINAL SURVEY PLATS

Thomas W. Steinke

PREPARED BY
THOMAS W. STEINKE P.S. #6177
LAND SURVEYING
106 PARK ST.
WAPAKONETA - OHIO
Ph 738-7421



FRYBURG EAST

CR# 110