



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.

Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.

Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date: _____

for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.

Signed: _____ Date: _____

Thomas W. Steinkamp
LAND SURVEYING
WAPAKONETA & BOTKINS, OHIO

Client LEO SCHWARTZ
County AUGLAIZE Twp. GERMAN Sec. 9 NW 1/4
Drawn by QWS Scale 1" = 100' Drwg. No. 77-389
Checked by _____ Date MAY 1977
Sheet _____ of _____ (T 7 S; R 4 E)

THOMAS W. STEINKE LAND SURVEYING



PHONE 419 738-7421

106 PARK ST.
WAPAKONETA, OHIO 45895

DESCRIPTION OF 4.000 ACRES

Being 4.000 Acres located in the north-west quarter of Section 9, Town-7-S, Range 4-E, German Township, Auglaize County, Ohio and being further described as follows:

Commencing at the south-west corner of the north-west quarter of Section 9, said point being marked by a railroad spike placed over an iron pipe, and the PLACE OF BEGINNING for the tract of land herein described.

Thence north with the center of Tri-Township Road T.R.# 31 and the west line of Section 9, a distance of 500.00 feet to a railroad spike.

Thence east with an interior angle of $89^{\circ} 41' 30''$, a distance of 348.48 feet to an iron pipe, passing through an iron pipe at 20.0 feet.

Thence south with an interior angle of $90^{\circ} 18' 30''$, a distance of 500.00 feet to the south line of B.B. 192 Pg. 183 and the east-west half section line of Section 9.

Thence west with the south line of said quarter section, an interior angle of $89^{\circ} 41' 30''$, a distance of 348.48 feet to a railroad spike and PLACE OF BEGINNING, passing through an iron pipe at 328.48 feet.

Containing in all 4.000 Acres and being subject to a 20.0 ft. half R/W on T.R. # 31.

Survey and description prepared by Thomas W. Steinke, registered surveyor # 6177 and recorded in Survey Book "C" Page 80 of the Auglaize County Survey Records.



81

81

| | |
|--|--|
| Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: _____ Date: _____ | Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: _____ Date: _____ |
| Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date: _____ | Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: _____ Date: _____ |
| Thomas W. Steinke LAND SURVEYING WAPAKONETA & BOTKINS, OHIO | Client <u>LEO SCHWARTZ</u> County <u>AUGLAIZE</u> Twp. <u>GERMAN</u> Sec. <u>9 NW 1/4</u> Drawn by <u>WWS</u> Scale <u>1" = 100'</u> Drwg. No. <u>77-389</u> Checked by _____ Date <u>MAY 1977</u> Sheet _____ of _____ (T 7 S; R 4 E) |

80

80a