



Signature by a representative of the County Health Dept.
 denotes compliance with Health Regulations.
 Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
 Planning Commission denotes approval of this plat.
 Signed: _____ Date _____

Signature by a representative of City with 3 mile limit juris-
 diction or Twp. Trustees or Village with zoning jurisdiction
 denotes approval of this plat. Signed: _____ Date _____

Signature by a representative of the County Engineer's Dept.
 denotes that this plat meets tax map plat requirements.
 Signed: _____ Date _____

THOMAS W. STEINKE
 Land Surveying
 106 Park Street
 Wapakoneta, Ohio 45885

Client **JOHN LAWLER**
 County **AUGLAIZE** Twp. **ST. MARYS** Sec. **2 S/W 1/4**
 Drawn by **G.E.M.** Scale **1" = 60'** Drwg. No. **77-257**
 Checked by **JLB** Date **JUNE 14-1977**
 Sheet **1** of **2** (T 6 S R 4 E)

THOMAS W. STEINKE

LAND SURVEYING



PHONE 419 738-7421

106 PARK ST.
WAPAKONETA, OHIO 45695

DESCRIPTION OF 2.106 ACRES

Being 2.106 Acres located in the S.W. quarter of Section 2, O.L.# 117, and O.L.# 118, T-6-S, R-4-E, St. Marys Township, Auglaize County, Ohio St. Marys City and being further described as follows:

Commencing at a stone found at the S.W. corner of Section 2, also being the S.W. corner of O.L.# 117.

Thence north with the west line of O.L. # 117 and the center of Beech Street, a distance of 300.00 feet to a railroad spike and PLACE OF BEGINNING for the tract of land herein described.

Thence continuing north with said center line and section line, a distance of 276.50 feet to a railroad spike.

Thence east with an interior angle of $92^{\circ} 02'$, a distance of 322.20 feet to an iron pipe.

Thence south with an interior angle of $87^{\circ} 58'$, a distance of 168.98 feet to an iron pipe.

Thence west with an interior angle of $90^{\circ} 44'$, a distance of 40.00 feet to an iron pipe,

Thence south-easterly with an interior angle of $308^{\circ} 17'$, a distance of 152.06 feet to an iron pipe.

Thence west with an interior angle of $51^{\circ} 01' 40''$, a distance of 377.73 feet to a railroad spike in the center line of Beech Street and the PLACE OF BEGINNING.

Containing in all 2.106 Acres of which 0.159 Acres is dedicated to road right-of-way.

Survey and description prepared by Thomas W. Steinke, registered surveyor # 6177 and recorded in Survey Book "C" Page 114 of the Auglaize County Survey Records.