



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date: _____
for political S. D. of: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

THOMAS W. STEINKE
 Land Surveying
 106 Park Street
 Wapakoneta, Ohio 45895

Client DONALD F. STEINKE
 County AUGLAIZE Twp. WASHINGTON Sec. 6 NW 1/4
 Drawn by JWS Scale 1"=200' Drwg. No. 17-436
 Checked by _____ Date JUNE 1977
 Sheet 1 of 2 127 (T 6 S R 4 E)

THOMAS W. STEINKE

LAND SURVEYING

PHONE 419 738-7421

106 PARK ST.
WAPAKONETA, OHIO 45655

Being 18.633 Acres located in the north-west quarter of Section 6, Town 6-S, Range 4-E, Washington Township, Auglaize County, Ohio and being the same lands as described in Deed Book 173, Page 549 and further described as follows:

Commencing at an iron pipe located at the south-west corner of the north-west quarter of Section 6.

Thence east with the east-west half section line of Section Six, a distance of 22.0 feet to an iron pipe and PLACE OF BEGINNING for the tract of land herein described.

Thence continuing east with said half section line, a distance of 702.75 feet to a corner post.

Thence north with an interior angle of $91^{\circ} 00'$, a distance of 1215.34 feet to a nail in the center of C.R.# 33-A, passing through an iron pipe at 1165.34 feet and a wood corner post at 1164.08 feet.

Thence west along the center line of C.R.# 33-A with a curve of a Radius of 28647.9 feet, Angle $00^{\circ} 58'$, Length 483.33, a distance of 410.06 feet to a point.

Thence west with said center line, an interior angle from the chord of a curve of $180^{\circ} 24' 30''$, a distance of 327.33 feet to a nail in the west line of Section 6.

Thence south with an interior angle of $100^{\circ} 04'$, a distance of 49.78 feet to the south R/W line of C.R.# 33-A.

Thence east with an interior angle of $79^{\circ} 56'$, a distance of 82.35 feet to a concrete monument.

Thence south with an interior angle of $280^{\circ} 04'$, a distance of 40.0 feet to a concrete monument.

Thence west with an interior angle of $259^{\circ} 56'$, a distance of 60.0 feet to a concrete monument 22.0 feet east of the west line of Section 6.

Thence south parallel to the west line of Section 6, an interior angle of $100^{\circ} 04'$, a distance of 1009.52 feet to an iron pipe and PLACE OF BEGINNING.

Containing in all 18.633 Acres with 0.83 Acres in road right-of-way.

Survey and description prepared by Thomas W. Steinke, registered surveyor # 6177 and recorded in Survey Book "C" Page 127 of the Auglaize County Survey Records.