



Scale:  
1" = 100'

D.B. 204  
P.G. 896

1/4 SEC. LINE

411.29

3.35 ACRES  
(0.24 AC IN ROAD R/W)  
EXIST HOUSE & SEWAGE

326.41 TO E

383.06 TO E

SEC. LINE

NAIL SET  
IN POST

(24.4)

97° 50'

415.19

NATIONAL ROAD

82° 10'

SE. COR.  
SEC. 25


(25.23)

931.22

171° 42' 30"

R.R. SPIKE SET  
OVER IRON PIN FD.

AUGLAIZE COUNTY  
SEC. COR. REF.



T-4-S  
R-4-E  
SEC 25  
SALEM TWP  
AUGLAIZE CO.

### LEGEND

- IRON PIPE SET
- R.R. SPIKE SET

"C" 133



Signature by a representative of the County Health Dept.  
denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

Signature by a representative of the Auglaize County Regional  
Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

Signature by a representative of City with 3 mile limit juris-  
diction or Twp. Trustees or Village with zoning jurisdiction  
denotes approval of this plat. Signed: \_\_\_\_\_ Date: \_\_\_\_\_  
for political S. D. of: \_\_\_\_\_

Signature by a representative of the County Engineer's Dept.  
denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

**133**  
THOMAS W. STEINKE  
Land Surveying  
106 Park Street  
Wapakoneta, Ohio 45895

Client JACK CORE  
County AUGLAIZE Twp. SALEM Sec. 25 3/4  
Drawn by WWS Scale 1" = 100' Drwg. No. 77-392  
Checked by \_\_\_\_\_ Date JUNE 1977  
Sheet \_\_\_\_\_ of \_\_\_\_\_ (T 4 S; R 4 E)

**133**

# THOMAS W. STEINKE

## LAND SURVEYING



PHONE 419 738-7421

106 PARK ST.  
WAPAKONETA, OHIO 45895

### DESCRIPTION OF 3.35 ACRES

Being 3.35 Acres located in the south-east quarter of Section 25, Town 4-South, Range 4-East, Salem Township, Auglaize County, Ohio and being further described as follows:

Commencing at the south-east corner of Section 25, said point being marked by a railroad spike and the center of National Road.

Thence north-west with the center line of National Road, a distance of 931.22 feet to a railroad spike and PLACE OF BEGINNING for the tract of land herein described:

Thence continuing north-westerly with said center line, a distance of 415.19 feet to a railroad spike.

Thence north with an interior angle of  $97^{\circ} 50'$ , a distance of 326.41 feet to an iron pipe, passing through a nail set in a corner post at 24.4 feet.

Thence east with an interior angle of  $90^{\circ} 00'$ , a distance of 411.29 feet to an iron pipe.

Thence south with an interior angle of  $90^{\circ} 00'$ , a distance of 383.06 feet to a railroad spike set in the center of National Road and PLACE OF BEGINNING, passing through an iron pipe at 357.83 feet and making an interior angle of  $82^{\circ} 10'$  with the beginning course.

Containing in all 3.35 Acres and being subject to 0.24 Acres in road right-of-way.

Survey and description prepared by Thomas W. Steinke, registered surveyor # 6177 and recorded in Survey Book "C" Page 133 of the Auglaize County Survey Records.

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: \_\_\_\_\_  
for political S. D. of: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

134 THOMAS W. STEINKE  
Land Surveying  
106 Park Street  
Wapakoneta, Ohio 45895

Client JACK CORE  
County AUGLAIZE Twp. SALEM Sec. 25 3/4  
Drawn by WWS Scale 1" = 100' Drwg. No. 17-392  
Checked by \_\_\_\_\_ Date JUNE 1977  
Sheet \_\_\_\_\_ of \_\_\_\_\_ (T 4 S; R 4 E)