SECTION LINES, HALF SECTION LINES & QUATER SECTION (ESTABLISHED BY DEEDS, MONUMENTATION FOUND, & OLD SURVEYS RECORDED WITH THE COUNTY ENGR. (CORNER 1326.9 1326.9 18 SECTION LINE NW. COR SE. QTR. SEC. 33 ALL EVIDER	DFFICE Scale:
TOWN 4 SOUTH OF SECTION 33 SEX OF LOGAN TOWNSHIP LE SOUNTY	 •
THOMAS W. STEINICE THOMAS W. STEINICE JOHN STEINICE ATT SECTION LINE LEGEND SURVEY BO	-
LEGRND ORRISPIKE SET PAGE X R.R. SPIKE FOUND O IRON PIPE SET X IRON BAR FOUND	
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date Date	
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: Signature by a representative of the County Engindenotes approval of this plat. Signed: Date Date	nts.
Thomas W. Fleinde Client CARL MACK LAND SURVEYING County AUGLAIZE Twp. LOGAN Sec. 33 WAYAKONETA & BOTKINS OHIO Drawn by QUIS Scale /"= 100' Drwg. No. 7 Checked by Date July 1977 Sheet / of 2 (TAs:	SE14 7-445

THOMAS W. STEINKE LAND SURVEYING



PHONE 419 738-7421

106 PARK ST. WAPAKONETA, OHIO 45395

DESCRIPTION OF 1.000 ACRES

Being 1.000 Acres located in the south-east quarter of Section 33, T-4-S, R-5-E, Logan Township, Auglaize County, Ohio and being further described as follows:

Commencing at a corner post located at the north-west corner of the south-east quarter of Section 33.

Thence east with the half section line of said section, a distance of 1326.9 feet to a railroad spike set in Conant Road and the quarter section line.

Thence south with an angle to the left of 89° 46°, along the quarter section line, a distance of 773.83 feet to a railroad spike and PLACE OF BEGINNING for the tract of land herein described.

Thence continuing south with said quarter section line, a distance of 180.00 feet to a railroad spike.

Thence east with an interior angle of 90° 00°, a distance of 242.00 feet to an iron pipe set, passing through an iron pipe at 20.0 feet.

Thence north with an interior angle of 90° 00', a distance of 180.00 feet to an iron pipe set.

Thence west with an interior angle of 90° 00°, a distance of 242.00 feet to a railroad spike and PLACE OF BEGINNING, passing an iron pipe at 222.01

Containing in all 1.000 Acres and being subject to all legal easements and rights-of-way of record.

Survey and description prepared by Thomas W. Steinke, registered surveyor # 6177 and recorded in Survey Book "C" Page /47 of the Auglaize County Survey Records.