

I gaomiy bion:

Peing two (2) contiguous parcels of land, one (1) cituated in the northeast quarter and the other in the southeast quarter of Section 18, T 7 S, R 4 E, German Township, Auglaize County, Ohio, and both more fully described as follows:

Scale:

Deginning at a point (said point being the southeast corner of the northeast quarter of Station 18 and marked by a harrow tooth over the corner stone); thence N 01° 00: E along the east line of the northeast quarter of Scation 18 for a distance of 100.00: to a point marked by a R. R. Spike set; thence westerly with an interior angle of 90° 03: bearing N 88° 57: W for a distance of 209.31: to a point in a drainage ditch passing through iron pipes set at 30.00: and 190.00: to mark the road right of way line and the ditch bank; thence southerly with an interior angle of 75° 55: bearing S 17° 02: E along the drainage ditch for a distance of 103.07: to a point on the south line of the northeast quarter of Section 18; thence casterly along the said south line with an interior angle of 104° 05: bearing S 88° 57: E for a distance of 184.30: to the point of beginning and passing through iron pipes set at 14.30: and 154.30: to mark the ditch bank and the road right of way line.

Tract No. 2 (southeast quarter)

Beginning at a point (said point being northeast corner of the southeast quarter of Section 18 and marked as for tract No. 1 above); thence S Ol° 00° W along the east line of Section 18 for a distance of 275.00° to a point where said east line intersects a drainage ditch and marked by a R. R. Spike set; thence northerly along the drainage ditch with an interior angle of 52° 16° and bearing N 51° 16° W for a distance of 121.90° to a point; thence northerly along the ditch with an interior angle of 151.4° bearing N 22° 40° W for a distance of 218.99° to a point; thence castarly with an interior angle of 66° 17° bearing S 88° 57° I for a distance of 184.30° to the point of reginning passing through iron pipes set at 14.30° and 154.30° to mark the ditch bank and the road right of way line.

The two parcels contains 1.274 cores, more or less, with .546 core in the northeast quarter and .728 core in the southeast quarter, and are subject to all legal highways consisting of .251 core...059 in NF h and .182 in SEA. and all respecting of manual.

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date Signature by a representative of the County Health Dept. denotes compliance with 12 the Regulations. Signed: Date		Signature by a (representative of the) County Commissioner(s) denotes approval of this plat. Signed:		