

NW COR.  
N.E. QTR  
SEC. 24  
T-5-S  
R-7-E  
UNION TWP.  
239.72

LES.R.#67

SURVEY BOOK "B" PAGE 256

Scale:  
1" = 100'




546.41

N 89° 44' 24" E

(35.3)

S 89° 58' 30" E

558.60



E RIMEHART RD # 245

PG 61

SURVEY BOOK "B"

N 00° 00' E

691.55

9.762 ACRES

0-IRON PIPE SET  
X-IRON PIN FOUND  
X-R.R. SPIKE FOUND

738.77

S 00° 00' 30" W

N 89° 44' 24" E

239.72

798.00

S 89° 44' 24" W



*Thomas W. Steinkamp*



SOUTH LINE OF  
D.B. 232 Pg 361

SURVEY BOOK "C" PAGE 204

WOOD COR. POST

Signature by a representative of the County Health Dept.  
denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the Auglaize County Regional  
Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of City with 3 mile limit juris-  
diction or Twp. Trustees or Village with zoning jurisdiction  
denotes approval of this plat. Signed: \_\_\_\_\_ Date \_\_\_\_\_  
for political S. D. of: \_\_\_\_\_

Signature by a representative of the County Engineer's Dept.  
denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

204

THOMAS W. STERNIE  
Land Surveying  
106 Park Street  
Wapakoneta, Ohio 45887

Client DARYL OSBORN  
County AUGLAIZE Twp. UNION Sec. 24  
Drawn by DWS Scale 1" = 100' Drwg. No. 481  
Checked by \_\_\_\_\_ Date AUGUST 1977  
Sheet \_\_\_\_\_ of \_\_\_\_\_ (T 5 S; R 7 E)

204

# THOMAS W. STEINKE

## LAND SURVEYING



PHONE 419 738-7421

106 PARK ST.  
WAPAKONETA, OHIO 45895

### Description of 9.762 Acres

Being 9.762 Acres located in the north-east quarter of Section 24, Town 5-S, Range 7-E, Union Township, Auglaize County, Ohio and being further described as follows:

Commencing at the north-west corner of the north-east quarter of Section 24, said point being the center line intersection of State Route # 67 and the Rinehart Road # 245.

Thence South  $00^{\circ} 00'$  East with the center line of Rinehart Road, a distance of 546.41 feet to a railroad spike.

Thence North  $89^{\circ} 44' 24''$  East, a distance of 239.72 feet to an iron pin.

Thence South  $00^{\circ} 00'$  East, a distance of 35.3 feet to an iron pipe and PLACE OF BEGINNING for the tract of land herein described:

Thence South  $89^{\circ} 58' 30''$  East, a distance of 558.60 feet to an iron pipe.

Thence South  $00^{\circ} 00' 30''$  West, a distance of 738.77 feet to a wood corner post.

Thence South  $89^{\circ} 44' 24''$  West, a distance of 798.0 feet to a railroad spike in the center of Rinehart Road.

Thence north  $00^{\circ} 00'$  East with said road, a distance of 50.00 feet to a railroad spike.

Thence North  $89^{\circ} 44' 24''$  East, a distance of 239.72 feet to an iron pin.

Thence North  $00^{\circ} 00'$  East, a distance of 691.55 feet to an iron pipe and PLACE OF BEGINNING.

Containing in all 9.762 Acres and being subject to all legal easements and R/W of record.

Survey and description prepared by Thomas W. Steinke, registered Surveyor # 6177 and recorded in Survey Book "C" Page 204 of the Auglaize County Survey Records.