


THIS SURVEY IS RECORDED IN BOOK "C" PAGE 258 OF THE AUGLAIZE CO. ENG. OFF.

LOCATION SITE



NOBLE TWP
SECTION 12
T-5-S-R-4-E
AUGLAIZE CO. O.

LEGEND

- R.R. SPIKE SET
- IRON PIPE SET
- ⊗ IRON PIPE FOUND
- ⊗ WOOD CORNER POST

ANGLES

- "A" 90° 34' 40"
- "B" 44° 32' 00"
- "C" 69° 29' 30"
- "D" 90° 00' 00"
- "E" 155° 58' 30"
- "F" 135° 28' 00"

WEST SECTION LINE

S/W COR.
N/W 1/4

1331.00

66A

EAST/WEST HALF SEC. LINE

R.R. SPIKE SET
OVER P.K. NAIL FD.

2.762 ACRES

615.62'

353.31'

267.83'

338.06'

66A

50' R/W

Scale:
1"=100'



Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date _____
for political S. D. of: _____

Post-It™ brand fax transmittal memo 7671		# of pages ▶ 1
To STEUP	From Doug	
Co. 1st AMER	Co. Aug CITY TAX MAP	
Dept.	Phone #	
Fax # 1-800-793-8124	Fax #	

THOMAS W. STIENNE
Land Surveying
385 Park Street
Cincinnati, Ohio 45202

Client JAMES JOHNS
County AUGLAIZE Twp. NOBLE Sec. 12
Drawn by G.E.M. Scale 1"=100' Drwg. No. 77-517
Checked by Date OCTOBER 5-1977
Sheet 1 of 2 (T-5-S-R-4-E)

258

258

THOMAS W. STEINKE

LAND SURVEYING



PHONE 419 738-7421

106 PARK ST.
WAPAKONETA, OHIO 45695

Description of 2.762 Acres.

Being 2.762 Acres located in the north-west quarter of Section 12, Town-5-S, Range-4-E, Noble Township, Auglaize County, Ohio and being further described as follows:

Commencing at the South-west corner of the north-west quarter of Section 12.

Thence east with the east-west half section line of Section 12, a distance of 1331.00 feet to a railroad spike at the intersection of C.R. 66-A.

Thence north with the center of C.R.# 66-A, an angle from the west of $90^{\circ} 34' 40''$, a distance of 896.17 feet to an iron pipe and PLACE OF BEGINNING for the tract of land herein described:

Thence continuing north with last described course, a distance of 615.62 feet to an iron pipe, said line being the west boundary of Deed Book 227, Page 408.

Thence easterly with an interior angle of $69^{\circ} 29' 30''$, a distance of 353.31 feet to a railroad spike in the center line of C.R.# 66-A, passing through an iron pipe at 328.31 feet.

Thence southerly with the center of C.R.# 66-A, and interior angle of $90^{\circ} 00'$, a distance of 267.83 feet to an iron pipe.

Thence south-west with the center line of C.R.# 66-A, an interior angle of $155^{\circ} 58' 30''$, a distance of 338.06 feet to an iron pipe and PLACE OF BEGINNING.

Containing in all 2.762 Acres and being subject to all legal easements and R/W of record.

Survey and description prepared by Thomas W. Steinke, registered surveyor # 6177 and recorded in Survey Book "C" Page 258 of the Auglaize County Survey Records.