

Scale:
1" = 100'

	SITE

MOULTON TWP.
SECTION 17 E 1/2
T. 5. S. R. 5. S
AUGLAIZE CO. OHIO

LEGEND

- O R.R. SPIKE FD.
 X IRON PIPE FD.
 O IRON PIPE SET

✓ C- MOULTON FORT AMADA RD.
C.R. 91

S/E COR
N/E 1/4

208.71'
KELLY ROAD C.R. 176

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

260

THOMAS H. STEWART
Land Surveying
100 Park Street
Wapakoneta, Ohio 45895

Client DAN HEITKAMP County AUGLAIZE Twp. MOULTON Sec. 17
 Drawn by G.E.M. Scale 1"=100 Drwg. No. 77-520
 Checked by JOS Date OCTOBER 11-1977
 Sheet 1 of 2 (T S S; R S E)

260

THOMAS W. STEINKE

LAND SURVEYING



PHONE 419 738-7421

106 PARK ST.
WAPAKONETA, OHIO 45895

Description of 1.000 Acre

Being 1.000 Acre located in the north-east quarter of Section 17, Town-5-S, Range-5-E, Moulton Township, Auglaize County, Ohio and being further described as follows:

Commencing at the south-east corner of the north-east quarter of Section 17 as called for in Deed Book 216, Page 751.

Thence west with the east-west half section line of Section 17 and the center line of Kelley Road # 176, a distance of 1315.85 feet to a railroad spike.

Thence north with an angle to the left from the east of $89^{\circ} 34'$, a distance of 208.71 feet to the PLACE OF BEGINNING for the tract of land herein described:

Thence continuing north with the last described course, a distance of 208.71 feet to an iron pipe.

Thence west with an interior angle of $89^{\circ} 34'$, a distance of 208.71 feet to an iron pipe.

Thence south with an interior angle of $90^{\circ} 26'$, a distance of 208.71 feet to an iron pipe.

Thence east with an interior angle of $89^{\circ} 34'$, a distance of 208.71 feet to the PLACE OF BEGINNING.

Containing in all 1.000 Acre and being subject to all legal easements of record.

Survey and description prepared by Thomas W. Steinke, registered surveyor, this 11th day of October, 1977 and recorded in Survey Book "C" Page 260 of the Auglaize County Survey Records.