


SEC. 8



UNION
TWP.

SECTION TIE & REFERENCE POINTS ARE TAKEN
FROM A SURVEY CONDUCTED BY CLAYTON H.
STIMMEL: DWG NO 72-5683 & 73-5775-A

LEGEND

- O = IRON PIPE SET
- X = IRON PIN FD.
- = R.R. SPIKE SET.
- X = R.R. SPIKE FD.

Scale:

1" = 100'



MILLER ROAD TR# 186



THIS SURVEY RECORDED IN SURVEY BOOK "C" PAGE 296

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
City/Twp. S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

296

THOMAS W. STEINKE
Land Surveying
105 Park Street
Cincinnati, Ohio

Client **MYRON SHAW**
County **AUGLAIZE** Twp. **UNION** Sec. **8**
Drawn by **RWS** Scale **1" = 100'** Drwg. No. **490**
Checked by **Tom** Date **Nov. 1977**
Sheet **5** of **7**

296

THOMAS W. STEINKE

LAND SURVEYING

PHONE 419 738-7421

105 PARK ST.
WAPAKONETA, OHIO 45885

DESCRIPTION OF 6.510 ACRES

Being 6.510 Acres located in the south-east quarter of Section 8, Town 5-S, Range 7-E, Union Township, Auglaize County, Ohio and being further described as follows:

Commencing at the north-east corner of the north-west quarter of the south-east quarter of Section 8, said point being marked with a railroad spike.

Thence North $89^{\circ} 30'$ West with the center line of Miller Road T.R.# 186 and the east-west half section line of Section 8, a distance of 452.44 feet to a railroad spike and PLACE OF BEGINNING for the tract of land herein described.

Thence South $01^{\circ} 22'$ West, a distance of 674.36 feet to an iron pipe.

Thence North $89^{\circ} 33'$ West, a distance of 420.43 feet to an iron pipe.

Thence North $01^{\circ} 22'$ East, a distance of 674.72 feet to a railroad spike in the center line of T.R.# 186 and the half section line of Section 8.

Thence South $89^{\circ} 30'$ East with said center line and half section line, a distance of 420.34 feet to a railroad spike and PLACE OF BEGINNING.

Containing in all 6.510 Acres and being subject to all legal easements and R/W of record.

Survey and description prepared by Thomas W. Steinke, registered surveyor # 6177 and recorded in Survey Book "C" Page 296 of the Auglaize County Survey Records.