


THIS SURVEY IS RECORDED IN BOOK "C" PAGE 313
OF THE AUGLAIZE COUNTY ENGINEERS OFFICE

THIS TRACT OF 1.568 AC IS PART OF A SURVEY CONDUCTED
BY CLAYTON H. STIMMEL 68-5428. OVERALL PARCEL OF 3.89
AC. HAS AN E/C 1'-30". USED EXISTING MONUMENTATION AS
FOUND IN THE FIELD FROM PREVIOUS SURVEY & STATE OF OHIO.




SURVEY CONDUCTED BY: Thomas W. Steinke
THOMAS W. STEINKE & ASSOCIATES INC.
WAPAKONETA, OHIO



1.568 ACRES

- LEGEND**
- ✕ IRON PIN FOUND
 - IRON PIPE SET
 - ✕ R.R. SPIKE FOUND
 - R.R. SPIKE SET
 - ⊙ CONC. RIW MON. FD.

LOCATION SITE



GERMAN TWP.
SECTION 10
T-7-S-R-4-E
AUGLAIZE CO. O.

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.

Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.

Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____

for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.

Signed: _____ Date: _____

THOMAS W. STEINKE
Land Surveying
106 Park Street
Wapakoneta, Ohio 45895

Client LEANDER LANDWEHR
County AUGLAIZE Twp. GERMAN Sec. 10
Drawn by G.E.M. Scale 1"=60' Drwg. No. 11-541
Checked by T.W.S. Date DECEMBER 30-1977
Sheet _____ of _____
(T-7-S-R-4-E)

THOMAS W. STEINKE

LAND SURVEYING



PHONE 419 738-7421

106 PARK ST.
WAPAKONETA, OHIO 45895

DESCRIPTION OF 1.568 ACRES

Being 1.568 Acres located in the north-east quarter of Section 10, Town 7-S, Range 4-E, German Township, Auglaize County, Ohio, and being further described as follows:

Commencing at the north-east corner of Section 10, said point being the center line intersection of Lock-Two Road and Quellhorst Road.

Thence south with the center line of Quellhorst Road, a distance of 767.92 feet to a railroad spike.

Thence continuing south with said center line with an angle from the north to the left of $165^{\circ} 40'$, a distance of 590.79 feet to an iron pipe.

Thence south-west with said center line with an angle from the last described course to the left of $154^{\circ} 05'$, a distance of 260.03 feet to a railroad spike and PLACE OF BEGINNING for the tract of land herein described.

Thence continuing south-west with the last described course and the center line of Quellhorst Road, a distance of 411.47 feet to a railroad spike.

Thence west with an interior angle of $90^{\circ} 00'$, a distance of 30.00 feet to a concrete R/W monument.

Thence west with an interior angle of $191^{\circ} 12' 40''$, a distance of 48.0 feet to a concrete monument in the east R/W line of State Route # 66.

Thence north along said R/W line with an interior angle of $109^{\circ} 23' 40''$, a distance of 374.72 feet to an iron pipe.

Thence east with an interior angle of $79^{\circ} 32' 40''$, a distance of 285.33 feet to a railroad spike in the center line of Quellhorst Road and the PLACE OF BEGINNING, passing through an iron pipe at 253.37 ft

Containing in all 1.568 Acres and being subject to all legal easements and R/W of record.

Survey and description prepared by Thomas W. Steinke & Assoc. Inc. this 9th day of January, 1978 and recorded in Survey Book C Page 314 of the Auglaize County Survey Records.