


THIS SURVEY IS RECORDED IN BOOK C PAGE 315
OF THE AUGLAIZE COUNTY ENGINEERS OFFICE
E- ALLEN-UNION-WAYNE RD.

Scale: 1"=60'

LOCATION



UNION TWP.
SECTION 1
T-5-S-R-8-E
AUGLAIZE CO. D.

LEGEND

- MON. BOX FD.
- ✕ R.R. SPIKE FD.
- R.R. SPIKE SET
- ✕ IRON PIPE FD.
- IRON PIPE SET
- CONC. COR POST



SURVEY CONDUCTED BY: Thomas W. Steinke
THOMAS W. STEINKE & ASSOCIATES INC.
WAPAKONETA, OHIO

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

THOMAS W. STEINKE
Land Surveying
106 Park Street
Wapakoneta, Ohio 45895

Client HELEN WARE MOX
County AUGLAIZE Twp. UNION Sec. ONE
Drawn by G.E.M. Scale 1"=60' Drwg. No. 17-553
Checked by T.W.S. Date JANUARY 6-78
Sheet 1 of 2
(T-5-S-R-8-E)

THOMAS W. STEINKE

LAND SURVEYING



PHONE 419 738-7421

106 PARK ST.
WAPAKONETA, OHIO 45895

DESCRIPTION OF 1.658 ACRES

Being 1.658 Acres located in the north-west quarter of Section 1, Town 5-S, Range 8-E, Union Township, Auglaize County, Ohio and being further described as follows:

Commencing at a monument box at the north-west corner of Section 1, said point being the center line intersection of Allen-Union-Wayne Road and Graham Road T.R.# 241.

Thence south with the west line of Section 1 and the center line of T.R.# 241, a distance of 1293.11 feet to a railroad spike and PLACE OF BEGINNING for the tract of land herein described.

Thence continuing south with said section line and center line, a distance of 343.75 feet to a railroad spike.

Thence east with an interior angle of $90^{\circ} 05' 20''$, a distance of 207.8 feet to an iron pipe, passing through a concrete post at 15.75 feet.

Thence north with an interior angle of $90^{\circ} 25' 40''$, a distance of 346.63 feet to an iron pipe.

Thence west with an interior angle of $88^{\circ} 48'$, a distance of 210.85 feet to a railroad spike and PLACE OF BEGINNING, passing through an iron pipe at 190.85 feet.

Containing in all 1.658 Acres and being subject to all legal easements and $\frac{1}{4}$ W of record.

Survey and description prepared by Thomas W. Steinke & Assoc., Inc. this 10th day of January, 1978 and recorded in Survey Book C Page 316 of the Auglaize County Survey Records.