


THIS SURVEY RECORDED IN SURVEY BOOK "C" PAGE 350



SEC. 30
NOBLE TWP.

Scale:
1" = 100'

N.W. COR SEC. 30
S 01° 01' W
319.15

S 50° 48' E
(44.52) 275.00
271.11
MONUMENT

(42.23)

STATE ROUTE # 33

THERE ARE NO BUILDINGS
LOCATED UPON THIS
4.00 AC TRACT.

4.00 Ac.

841.57' TO

LEGEND

- ✕: R.R. SPIKE PD.
- ⊗: IRON PIPE PD
- : IRON PIPE SET.



SEE SURVEY BOOK "C" PAGE 209

SURVEY CONDUCTED BY: *Thomas W. Steinke*
THOMAS W. STEINKE & ASSOCIATES INC.
WAPAKONETA, OHIO



THIS SURVEY IS BASED ON A BOUNDARY
SURVEY CONDUCTED BY C.H. STIMMEL
#68-5448 DATED: 10-6-68
DEED BOOK 217 PAGE 91

SW. COR.
NW. QTR.
N.W. QTR, SEC 30

155.32

N 83° 49' W

1/4 SEC. LINE

MERCER COUNTY

N 01° 01' E

WEST LINE OF AUGLAIZE COUNTY

1008.91' TO

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

THOMAS W. STEINKE
Land Surveying
106 Park Street
Wapakoneta, Ohio 45895

Client RE. SAINTIGNON
County AUGLAIZE Twp. Noble Sec. 30 NW 1/4
Drawn by JWS Scale 1"=100' Drwg. No. 78-582
Checked by _____ Date February 25, 1978
Sheet _____ of _____ (T 5 S: R 4)

350

350

THOMAS W. STEINKE

LAND SURVEYING



PHONE 419 733-7421

106 PARK ST.
WAPAKONETA, OHIO 45885

DESCRIPTION OF 4.00 ACRES

Being 4.00 Acres located in the north-west quarter of Section 30, Town 5-S, Range 4-E, Noble Township, Auglaize County, Ohio and being further described as follows:

Commencing at a railroad spike located at the north-west corner of Section 30.

Thence South $01^{\circ} 01'$ West with the west line of Section 30 and the west line of Auglaize County, a distance of 319.15 feet to a railroad spike in the center line of State Route #33 and the PLACE OF BEGINNING for the tract of land herein described.

Thence South $50^{\circ} 48'$ East, with the center line of S.R.#33, a distance of 275.00 feet to a point.

Thence South $05^{\circ} 10'$ West, a distance of 841.57 feet to an iron pipe, passing through an iron pipe at 42.23 feet.

Thence North $88^{\circ} 49'$ West, a distance of 155.32 feet to a corner stone at the south-west corner of the north-west quarter of the north-west quarter of Section 30.

Thence North $01^{\circ} 01'$ East with the west line of Section 30, a distance of 1008.91 feet to a railroad spike and PLACE OF BEGINNING, passing through an iron pipe at 964.39 feet.

Containing in all 4.000 Acres and being subject to 0.22 Acre in road right-of-way.

Survey and description prepared by Thomas W. Steinke & Assoc., Inc. this 27th day of February, 1978 and recorded in Survey Book C Page 350 of the Auglaize County Survey Records.